


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:24.00V I:0.3316A P:7.958W PF:1.000 Freq:0Hz Lamp Flux:404.569x1 lm		
NAME: NNR18	TYPE:	WEIGHT:
SPEC.:NNR18-9LWNW24CSN050CC0100	DIM.: 1000*18mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*18	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 50.84 lm/W			
MODEL	NNR18	I _{max} (cd)	70.17	S/MH(C0/180)	1.62
NOMINAL POWER(W)	7.2	LOR(%)	100.0	S/MH(C90/270)	1.25
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	404.57	h UP,DN(C0-180)	12.1,37.4
NOMINAL FLUX(lm)	404.569	CIE CLASS	SEMI-D.	h UP,DN(C180-360)	12.4,38.1
LAMPS INSIDE	1	h up(%)	24.4	CIBSE SHR NOM	1.50
TEST VOLTAGE(V)	24	h down(%)	75.6	CIBSE SHR MAX	1.55



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-07-10

g Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	61.78	60.54	59.57	60.86	62.46	61.05	59.51	60.44	0- 10	5.809	5.809	1.44,1.44
20	62.99	59.61	56.13	60.62	64.59	60.76	56.13	59.49	10- 20	17.13	22.94	5.67,5.67
30	64.18	57.85	50.69	59.78	66.94	59.79	50.84	57.70	20- 30	27.44	50.38	12.5,12.5
40	65.34	55.12	43.58	58.23	68.98	58.12	43.58	54.96	30- 40	35.97	86.35	21.3,21.3
50	65.87	51.95	35.07	55.94	70.03	55.68	35.11	51.69	40- 50	42.09	128.4	31.7,31.7
60	65.70	48.52	25.66	53.06	70.12	52.73	25.67	48.23	50- 60	45.51	173.9	43,43
70	64.55	45.22	15.79	49.80	69.37	49.44	15.78	44.95	60- 70	46.19	220.1	54.4,54.4
80	62.56	42.03	6.480	46.32	67.53	45.88	6.481	41.72	70- 80	44.55	264.7	65.4,65.4
90	58.51	37.98	0.5783	42.09	63.96	41.50	0.5120	38.13	80- 90	40.97	305.7	75.6,75.6
100	51.89	31.66	0.2805	33.95	57.23	33.10	0.2473	28.70	90-100	36.12	341.8	84.5,84.5
110	41.31	23.45	0.2938	23.07	44.79	22.39	0.3809	21.94	100-110	27.62	369.4	91.3,91.3
120	30.14	14.54	0.5054	12.15	32.07	12.17	0.5010	15.36	110-120	18.27	387.7	95.8,95.8
130	19.32	8.257	0.6147	4.071	19.63	3.942	0.5879	9.384	120-130	10.27	397.9	98.4,98.4
140	9.661	3.072	0.6809	0.9550	8.382	0.9892	0.6679	3.920	130-140	4.420	402.4	99.5,99.5
150	2.246	0.9475	0.8090	0.9351	1.028	0.9418	0.7347	1.908	140-150	1.384	403.7	99.8,99.8
160	1.109	0.8617	0.8283	0.9752	0.9151	0.9418	0.8618	1.070	150-160	0.4710	404.2	99.9,99.9
170	0.9623	0.9287	0.9551	1.022	0.8416	0.9485	0.9823	0.8817	160-170	0.2660	404.5	100,100
180	0.8750	1.069	1.055	1.082	0.8483	1.069	1.069	1.055	170-180	0.0921	404.6	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-07-10

g Range: 0 - 180DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:24.00V I:0.3316A P:7.958W PF:1.000 Freq:0Hz Lamp Flux:404.569x1 lm		
NAME: NNR18	TYPE:	WEIGHT:
SPEC.:NNR18-9LWNW24CSN050CC0100	DIM.: 1000*18mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*18	Shielding Angle:



LUMINANCE cd/(m2)		
G(180)	C0/180	C90/270
85	38682	1757
80	20016	2073
75	13676	2355
70	10485	2565
65	8568	2726
60	7300	2851
55	6381	2951
50	5693	3031
45	5170	3101


C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-07-10

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:24.00V I:0.3316A P:7.958W PF:1.000 Freq:0Hz Lamp Flux:404.569x1 lm		
NAME: NNR18	TYPE:	WEIGHT:
SPEC.:NNR18-9LWNW24CSN050CC0100	DIM.: 1000*18mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*18	Shielding Angle:

r _{cc}	80%			70%			50%			30%			10%			0
r _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Coefficients of Utilization(CU)															
0.0	1.13	1.13	1.13	1.08	1.08	1.08	.98	.98	.98	.88	.88	.88	.80	.80	.80	.76
1.0	.92	.86	.81	.87	.82	.77	.78	.74	.70	.70	.67	.64	.63	.60	.58	.54
2.0	.78	.69	.62	.74	.66	.60	.66	.60	.55	.59	.54	.50	.53	.49	.45	.41
3.0	.67	.57	.50	.63	.55	.48	.57	.50	.44	.51	.45	.40	.45	.40	.36	.33
4.0	.58	.49	.41	.55	.46	.39	.50	.42	.36	.44	.38	.33	.40	.34	.30	.27
5.0	.52	.42	.35	.49	.40	.33	.44	.36	.31	.39	.33	.28	.35	.30	.26	.23
6.0	.46	.36	.30	.44	.35	.28	.39	.32	.26	.35	.29	.24	.32	.26	.22	.19
7.0	.41	.32	.26	.39	.31	.25	.36	.28	.23	.32	.26	.21	.29	.23	.19	.17
8.0	.38	.29	.22	.36	.27	.22	.32	.25	.20	.29	.23	.19	.26	.21	.17	.15
9.0	.34	.26	.20	.33	.25	.19	.30	.23	.18	.27	.21	.16	.24	.19	.15	.13
10.0	.31	.23	.18	.30	.22	.17	.27	.21	.16	.25	.19	.15	.22	.17	.14	.12



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-07-10

g Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:24.00V I:0.3316A P:7.958W PF:1.000 Freq:0Hz Lamp Flux:404.569x1 lm		
NAME: NNR18	TYPE:	WEIGHT:
SPEC.:NNR18-9LWNW24CSN050CC0100	DIM.: 1000*18mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*18	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Wall Exitance Coefficients(WEC)															
0.0																
1.0	.424	.241	.076	.409	.233	.074	.381	.219	.070	.356	.205	.066	.333	.193	.062	
2.0	.356	.195	.060	.343	.189	.058	.318	.177	.055	.294	.165	.052	.273	.154	.049	
3.0	.311	.166	.050	.299	.160	.048	.276	.150	.046	.255	.140	.043	.236	.130	.040	
4.0	.277	.144	.042	.266	.139	.041	.245	.130	.039	.226	.121	.037	.208	.113	.034	
5.0	.250	.127	.037	.240	.123	.036	.221	.115	.034	.204	.107	.032	.187	.100	.030	
6.0	.228	.114	.033	.219	.110	.032	.201	.103	.030	.185	.096	.028	.170	.090	.027	
7.0	.209	.103	.029	.201	.100	.029	.185	.094	.027	.170	.087	.025	.156	.081	.024	
8.0	.193	.094	.027	.186	.091	.026	.171	.085	.024	.157	.080	.023	.144	.074	.022	
9.0	.180	.087	.024	.173	.084	.024	.159	.079	.022	.146	.073	.021	.134	.068	.020	
10.0	.168	.080	.022	.161	.078	.022	.149	.073	.021	.137	.068	.019	.126	.063	.018	

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Ceiling Cavity Exitance Coefficients(CCEC)															
0.0	.377	.377	.377	.322	.322	.322	.220	.220	.220	.126	.126	.126	.040	.040	.040	
1.0	.376	.343	.313	.322	.294	.270	.220	.202	.186	.127	.117	.108	.041	.038	.035	
2.0	.370	.321	.279	.317	.276	.241	.217	.191	.168	.125	.111	.099	.040	.036	.032	
3.0	.363	.305	.259	.311	.263	.224	.213	.183	.157	.123	.107	.093	.040	.035	.030	
4.0	.355	.293	.245	.304	.253	.213	.209	.176	.150	.121	.103	.089	.039	.034	.029	
5.0	.347	.283	.236	.298	.245	.205	.205	.171	.145	.119	.100	.086	.038	.033	.028	
6.0	.339	.275	.229	.292	.238	.200	.201	.167	.141	.117	.098	.084	.038	.032	.028	
7.0	.332	.269	.224	.286	.233	.196	.197	.163	.139	.115	.096	.082	.037	.032	.027	
8.0	.325	.263	.221	.280	.228	.192	.194	.160	.137	.113	.095	.081	.036	.031	.027	
9.0	.319	.259	.218	.275	.224	.190	.190	.158	.135	.111	.093	.080	.036	.031	.027	
10.0	.313	.254	.216	.270	.221	.188	.187	.155	.134	.109	.092	.080	.035	.030	.026	

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-07-10

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:24.00V I:0.3316A P:7.958W PF:1.000 Freq:0Hz Lamp Flux:404.569x1 lm										
NAME: NNR18					TYPE:			WEIGHT:		
SPEC.:NNR18-9LWNW24CSN050CC0100					DIM.: 1000*18mm			SERIAL No.:01		
MFR.: COLORS					SUR.:1000*18			Shielding Angle:		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	21.3	22.7	21.9	23.3	24.0	18.1	19.4	18.7	20.0	20.7
3H	24.6	25.8	25.2	26.5	27.2	19.7	21.0	20.3	21.6	22.3
4H	26.4	27.6	27.1	28.3	29.0	20.4	21.6	21.1	22.3	23.0
6H	28.5	29.6	29.1	30.3	31.1	20.9	22.1	21.6	22.7	23.5
8H	29.6	30.7	30.3	31.4	32.2	21.1	22.2	21.8	22.9	23.7
12H	30.9	32.0	31.6	32.7	33.5	21.2	22.3	21.9	23.0	23.8
4H 2H	21.9	23.1	22.5	23.7	24.5	19.7	20.9	20.3	21.5	22.3
3H	25.4	26.4	26.0	27.1	27.9	21.7	22.8	22.4	23.5	24.3
4H	27.4	28.3	28.1	29.0	29.9	22.7	23.6	23.4	24.4	25.2
6H	29.6	30.5	30.4	31.2	32.1	23.5	24.3	24.2	25.1	25.9
8H	30.9	31.7	31.7	32.5	33.4	23.8	24.6	24.5	25.3	26.2
12H	32.4	33.1	33.1	33.9	34.8	24.0	24.8	24.8	25.5	26.4
8H 4H	27.7	28.6	28.5	29.3	30.2	24.3	25.1	25.0	25.8	26.7
6H	30.3	31.0	31.1	31.8	32.7	25.6	26.3	26.4	27.1	28.0
8H	31.8	32.4	32.6	33.2	34.1	26.2	26.8	27.0	27.6	28.5
12H	33.5	34.0	34.3	34.8	35.8	26.7	27.2	27.5	28.0	29.0
12H 4H	27.8	28.5	28.5	29.3	30.2	24.8	25.6	25.5	26.3	27.2
6H	30.4	31.1	31.2	31.9	32.8	26.4	27.0	27.2	27.8	28.8
8H	32.0	32.6	32.8	33.4	34.3	27.3	27.8	28.1	28.6	29.6
Variations with the observer position at spacings:										
S = 1.0H	+ 0.1 / - 0.1					+ 0.1 / - 0.1				
1.5H	+ 0.2 / - 0.2					+ 0.2 / - 0.3				
2.0H	+ 0.2 / - 0.3					+ 0.3 / - 0.4				

CIE Pub.117, 404.6 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -3.1)

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-07-10

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:24.00V I:0.3316A P:7.958W PF:1.000 Freq:0Hz Lamp Flux:404.569x1 lm		
NAME: NNR18	TYPE:	WEIGHT:
SPEC.:NNR18-9LWNW24CSN050CC0100	DIM.: 1000*18mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*18	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	43	30	23	42	30	23	40	29	22	15
0.80	52	38	30	50	37	29	47	36	28	20
1.00	59	45	36	57	44	36	53	45	35	25
1.25	66	52	43	64	51	42	59	48	41	30
1.50	71	58	49	68	56	47	63	53	45	34
2.00	79	67	57	76	64	56	69	60	53	40
2.50	84	72	63	80	70	61	73	64	58	43
3.00	88	77	69	84	74	66	76	68	62	47
4.00	93	84	76	88	80	73	80	74	68	52
5.00	96	88	81	91	84	78	83	77	72	55
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-07-10

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:24.00V I:0.3316A P:7.958W PF:1.000 Freq:0Hz Lamp Flux:404.569x1 lm		
NAME: NNR18	TYPE:	WEIGHT:
SPEC.:NNR18-9LWNW24CSN050CC0100	DIM.: 1000*18mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*18	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-07-10

Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

AAI Figure

Test:U:24.00V I:0.3316A P:7.958W PF:1.000 Freq:0Hz Lamp Flux:404.569x1 lm		
NAME: NNR18	TYPE:	WEIGHT:
SPEC.:NNR18-9LWNW24CSN050CC0100	DIM.: 1000*18mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*18	Shielding Angle:

Flux out:297.8 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-07-10

g Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:24.00V I:0.3316A P:7.958W PF:1.000 Freq:0Hz Lamp Flux:404.569x1 lm		
NAME: NNR18	TYPE:	WEIGHT:
SPEC.:NNR18-9LWNW24CSN050CC0100	DIM.: 1000*18mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*18	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-07-10

Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:24.00V I:0.3316A P:7.958W PF:1.000 Freq:0Hz Lamp Flux:404.569x1 lm		
NAME: NNR18	TYPE:	WEIGHT:
SPEC.:NNR18-9LWNW24CSN050CC0100	DIM.: 1000*18mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*18	Shielding Angle:


AvgL	cd/m2
L_0~180(65)av	8875
L_0~180(75)av	14203
L_0~180(85)av	40317
L_90~270(65)av	2725
L_90~270(75)av	2355
L_90~270(85)av	1780
L_45(65)av	6442
L_45(75)av	9810
L_45(85)av	26801

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-07-10

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2021-07-10

deg Range: 0 - 180DEG
deg Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:24.00V I:0.3316A P:7.958W PF:1.000 Freq:0Hz Lamp Flux:404.569x1 lm		
NAME: NNR18	TYPE:	WEIGHT:
SPEC.:NNR18-9LWNW24CSN050CC0100	DIM.: 1000*18mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*18	Shielding Angle:

Table--1

UNIT: cd

C(DEG) g (DEG)	0	45	90	135	180	225	270	315										
0	61.4	60.9	60.6	60.8	61.4	60.9	60.6	60.8										
5	61.3	60.8	60.4	60.9	61.7	61.0	60.4	60.7										
10	61.8	60.5	59.6	60.9	62.5	61.1	59.5	60.4										
15	62.4	60.2	58.1	60.8	63.5	61.0	58.1	60.1										
20	63.0	59.6	56.1	60.6	64.6	60.8	56.1	59.5										
25	63.6	58.8	53.6	60.3	65.7	60.4	53.7	58.7										
30	64.2	57.8	50.7	59.8	66.9	59.8	50.8	57.7										
35	64.8	56.6	47.4	59.1	68.1	59.0	47.5	56.4										
40	65.3	55.1	43.6	58.2	69.0	58.1	43.6	55.0										
45	65.8	53.6	39.5	57.2	69.6	57.0	39.5	53.4										
50	65.9	51.9	35.1	55.9	70.0	55.7	35.1	51.7										
55	65.9	50.3	30.5	54.6	70.2	54.2	30.8	50.0										
60	65.7	48.5	25.7	53.1	70.1	52.7	25.7	48.2										
65	65.2	46.8	20.7	51.5	69.9	51.1	20.7	46.6										
70	64.6	45.2	15.8	49.8	69.4	49.4	15.8	45.0										
75	63.7	43.6	11.0	48.1	68.6	47.7	11.0	43.4										
80	62.6	42.0	6.48	46.3	67.5	45.9	6.48	41.7										
85	60.7	40.3	2.76	44.3	65.8	43.7	2.83	40.0										
90	58.5	38.0	0.58	42.1	64.0	41.5	0.51	38.1										
95	56.2	35.6	0.34	39.6	62.1	38.8	0.23	35.8										
100	51.9	31.7	0.28	33.9	57.2	33.1	0.25	28.7										
105	46.7	27.9	0.27	28.4	51.1	27.6	0.32	26.9										
110	41.3	23.5	0.29	23.1	44.8	22.4	0.38	21.9										
115	35.7	19.0	0.41	16.9	38.4	16.7	0.43	19.0										
120	30.1	14.5	0.51	12.2	32.1	12.2	0.50	15.4										
125	24.6	11.0	0.92	7.87	25.8	7.85	0.56	12.4										
130	19.3	8.26	0.61	4.07	19.6	3.94	0.59	9.38										
135	14.2	5.42	0.62	1.64	14.1	1.54	0.63	5.64										
140	9.66	3.07	0.68	0.96	8.38	0.99	0.67	3.92										
145	4.98	1.54	0.94	0.94	3.36	0.94	0.70	2.66										
150	2.25	0.95	0.81	0.94	1.03	0.94	0.73	1.91										
155	1.18	0.85	0.80	0.95	0.94	0.94	0.79	1.43										
160	1.11	0.86	0.83	0.98	0.92	0.94	0.86	1.07										
165	1.07	0.88	0.94	0.98	0.88	0.95	0.92	0.89										
170	0.96	0.93	0.96	1.02	0.84	0.95	0.98	0.88										
175	0.88	1.01	1.04	1.06	0.84	0.96	1.06	0.96										
180	0.88	1.07	1.06	1.08	0.85	1.07	1.07	1.06										

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-07-10

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks: