


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:24.00V I:0.3350A P:8.039W PF:1.000 Freq:0Hz Lamp Flux:345.539x1 lm		
NAME: NNR18	TYPE:	WEIGHT:
SPEC.:NNR18-9LWNW24CSN050CC0100	DIM.: 1000*18mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*18	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 42.98 lm/W			
MODEL	NNR18	I _{max} (cd)	59.94	S/MH(C0/180)	1.62
NOMINAL POWER(W)	7.2	LOR(%)	100.0	S/MH(C90/270)	1.25
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	345.54	h UP,DN(C0-180)	12.0,37.5
NOMINAL FLUX(lm)	345.539	CIE CLASS	SEMI-D.	h UP,DN(C180-360)	12.4,38.2
LAMPS INSIDE	1	h up(%)	24.4	CIBSE SHR NOM	1.50
TEST VOLTAGE(V)	24	h down(%)	75.6	CIBSE SHR MAX	1.55



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-07-10

g Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	52.89	51.83	50.96	52.02	53.49	52.27	50.92	51.71	0- 10	4.971	4.971	1.44,1.44
20	53.92	51.06	48.01	51.79	55.30	52.03	48.03	50.89	10- 20	14.66	19.63	5.68,5.68
30	54.96	49.52	43.33	51.04	57.30	51.18	43.51	49.32	20- 30	23.48	43.11	12.5,12.5
40	56.01	47.23	37.21	49.66	58.99	49.72	37.29	46.98	30- 40	30.77	73.88	21.4,21.4
50	56.46	44.57	30.01	47.70	59.86	47.63	30.07	44.18	40- 50	36.01	109.9	31.8,31.8
60	56.31	41.65	21.93	45.17	59.88	45.09	21.97	41.24	50- 60	38.94	148.8	43.1,43.1
70	55.28	38.81	13.50	42.37	59.22	42.28	13.49	38.40	60- 70	39.48	188.3	54.5,54.5
80	53.57	36.07	5.537	39.38	57.65	39.21	5.555	35.61	70- 80	38.07	226.4	65.5,65.5
90	50.03	32.40	0.4865	35.75	54.56	35.47	0.4205	32.47	80- 90	34.96	261.3	75.6,75.6
100	44.16	26.97	0.2405	28.83	48.78	28.41	0.2143	24.54	90-100	30.83	292.2	84.6,84.6
110	35.04	19.79	0.2871	19.68	38.28	19.42	0.3407	18.74	100-110	23.53	315.7	91.4,91.4
120	25.43	12.00	0.4073	10.50	27.53	10.76	0.4209	12.75	110-120	15.55	331.3	95.9,95.9
130	16.13	6.821	0.5412	3.591	17.03	3.673	0.5014	7.623	120-130	8.733	340.0	98.4,98.4
140	7.843	2.402	0.5994	0.8149	7.495	0.8356	0.5680	3.040	130-140	3.721	343.7	99.5,99.5
150	1.647	0.7545	0.7018	0.7949	0.8675	0.8149	0.6412	1.383	140-150	1.143	344.8	99.8,99.8
160	0.9418	0.7347	0.7281	0.8216	0.7548	0.8149	0.7351	0.7761	150-160	0.3871	345.2	99.9,99.9
170	0.8152	0.8016	0.8283	0.8817	0.7346	0.8215	0.8418	0.7414	160-170	0.2248	345.5	100,100
180	0.7548	0.8550	0.8951	0.9151	0.7414	0.8550	0.9151	0.9017	170-180	0.0784	345.5	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-07-10

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:24.00V I:0.3350A P:8.039W PF:1.000 Freq:0Hz Lamp Flux:345.539x1 lm		
NAME: NNR18	TYPE:	WEIGHT:
SPEC.:NNR18-9LWNW24CSN050CC0100	DIM.: 1000*18mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*18	Shielding Angle:



LUMINANCE cd/(m2)		
G(180)	C0/180	C90/270
85	33010	1453
80	17138	1772
75	11711	2014
70	8980	2192
65	7337	2332
60	6257	2437
55	5468	2524
50	4880	2594
45	4431	2651


C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-07-10

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:24.00V I:0.3350A P:8.039W PF:1.000 Freq:0Hz Lamp Flux:345.539x1 lm		
NAME: NNR18	TYPE:	WEIGHT:
SPEC.:NNR18-9LWNW24CSN050CC0100	DIM.: 1000*18mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*18	Shielding Angle:

r _{cc}	80%			70%			50%			30%			10%			0
r _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Coefficients of Utilization(CU)															
0.0	1.13	1.13	1.13	1.08	1.08	1.08	.98	.98	.98	.88	.88	.88	.80	.80	.80	.76
1.0	.92	.86	.81	.87	.82	.77	.78	.74	.70	.70	.67	.64	.63	.60	.58	.54
2.0	.78	.69	.62	.74	.66	.60	.66	.60	.55	.59	.54	.50	.53	.49	.45	.41
3.0	.67	.58	.50	.63	.55	.48	.57	.50	.44	.51	.45	.40	.45	.40	.36	.33
4.0	.58	.49	.41	.55	.46	.39	.50	.42	.36	.44	.38	.33	.40	.34	.30	.27
5.0	.52	.42	.35	.49	.40	.33	.44	.36	.31	.39	.33	.28	.35	.30	.26	.23
6.0	.46	.36	.30	.44	.35	.28	.39	.32	.26	.35	.29	.24	.32	.26	.22	.19
7.0	.41	.32	.26	.39	.31	.25	.36	.28	.23	.32	.26	.21	.29	.23	.19	.17
8.0	.38	.29	.22	.36	.27	.22	.32	.25	.20	.29	.23	.19	.26	.21	.17	.15
9.0	.34	.26	.20	.33	.25	.19	.30	.23	.18	.27	.21	.17	.24	.19	.15	.13
10.0	.31	.23	.18	.30	.22	.17	.27	.21	.16	.25	.19	.15	.22	.17	.14	.12



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-07-10

g Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:24.00V I:0.3350A P:8.039W PF:1.000 Freq:0Hz Lamp Flux:345.539x1 lm		
NAME: NNR18	TYPE:	WEIGHT:
SPEC.:NNR18-9LWNW24CSN050CC0100	DIM.: 1000*18mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*18	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Wall Exitance Coefficients(WEC)															
0.0																
1.0	.424	.241	.076	.409	.233	.074	.381	.219	.070	.356	.205	.066	.333	.193	.062	
2.0	.356	.195	.060	.343	.189	.058	.318	.177	.055	.295	.165	.052	.273	.155	.049	
3.0	.311	.166	.050	.299	.160	.048	.276	.150	.046	.255	.140	.043	.236	.131	.040	
4.0	.277	.144	.042	.266	.139	.041	.246	.130	.039	.226	.122	.037	.208	.113	.034	
5.0	.250	.127	.037	.240	.123	.036	.221	.115	.034	.204	.107	.032	.187	.100	.030	
6.0	.228	.114	.033	.219	.110	.032	.201	.103	.030	.185	.096	.028	.170	.090	.027	
7.0	.209	.103	.029	.201	.100	.029	.185	.094	.027	.170	.087	.025	.156	.081	.024	
8.0	.193	.094	.027	.186	.091	.026	.171	.085	.024	.157	.080	.023	.144	.074	.022	
9.0	.180	.087	.024	.173	.084	.024	.159	.079	.022	.146	.073	.021	.134	.068	.020	
10.0	.168	.080	.022	.161	.078	.022	.149	.073	.021	.137	.068	.019	.126	.063	.018	

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Ceiling Cavity Exitance Coefficients(CCEC)															
0.0	.376	.376	.376	.321	.321	.321	.219	.219	.219	.126	.126	.126	.040	.040	.040	
1.0	.375	.342	.313	.321	.294	.269	.220	.202	.186	.126	.117	.108	.041	.038	.035	
2.0	.369	.320	.279	.316	.275	.241	.217	.191	.168	.125	.111	.098	.040	.036	.032	
3.0	.362	.304	.258	.310	.262	.224	.213	.182	.157	.123	.106	.092	.040	.035	.030	
4.0	.354	.292	.244	.304	.252	.212	.209	.176	.150	.121	.103	.088	.039	.034	.029	
5.0	.346	.282	.235	.297	.244	.205	.205	.171	.144	.119	.100	.086	.038	.033	.028	
6.0	.339	.275	.229	.291	.238	.199	.201	.166	.141	.116	.098	.084	.038	.032	.028	
7.0	.331	.268	.224	.285	.232	.195	.197	.163	.138	.114	.096	.082	.037	.031	.027	
8.0	.324	.263	.220	.279	.228	.192	.193	.160	.136	.112	.094	.081	.036	.031	.027	
9.0	.318	.258	.217	.274	.224	.189	.190	.157	.135	.111	.093	.080	.036	.030	.027	
10.0	.312	.254	.215	.269	.220	.188	.187	.155	.133	.109	.092	.080	.035	.030	.026	

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-07-10

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:24.00V I:0.3350A P:8.039W PF:1.000 Freq:0Hz Lamp Flux:345.539x1 lm										
NAME: NNR18					TYPE:			WEIGHT:		
SPEC.:NNR18-9LWNW24CSN050CC0100					DIM.: 1000*18mm			SERIAL No.:01		
MFR.: COLORS					SUR.:1000*18			Shielding Angle:		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise				Viewed endwise				
x = 2H y = 2H	21.4	22.7	21.9	23.3	24.0	18.1	19.5	18.7	20.1	20.8
	3H 24.6	25.9	25.2	26.5	27.2	19.8	21.0	20.4	21.6	22.4
	4H 26.5	27.6	27.1	28.3	29.1	20.4	21.6	21.1	22.3	23.0
	6H 28.5	29.6	29.2	30.3	31.1	21.0	22.1	21.6	22.8	23.5
	8H 29.7	30.7	30.3	31.4	32.2	21.1	22.2	21.8	22.9	23.7
	12H 30.9	32.0	31.6	32.7	33.5	21.2	22.3	21.9	23.0	23.8
4H	2H 21.9	23.1	22.6	23.8	24.5	19.7	20.9	20.4	21.6	22.3
	3H 25.4	26.4	26.1	27.1	27.9	21.7	22.8	22.4	23.5	24.3
	4H 27.4	28.4	28.1	29.1	29.9	22.7	23.7	23.4	24.4	25.2
	6H 29.7	30.5	30.4	31.3	32.1	23.5	24.4	24.2	25.1	26.0
	8H 30.9	31.8	31.7	32.5	33.4	23.8	24.6	24.5	25.4	26.3
	12H 32.4	33.1	33.1	33.9	34.8	24.0	24.8	24.8	25.5	26.4
8H	4H 27.8	28.6	28.5	29.3	30.2	24.3	25.1	25.0	25.9	26.7
	6H 30.3	31.0	31.1	31.8	32.7	25.6	26.3	26.4	27.1	28.0
	8H 31.8	32.4	32.6	33.2	34.2	26.2	26.8	27.0	27.6	28.6
	12H 33.5	34.0	34.3	34.8	35.8	26.7	27.3	27.5	28.1	29.0
12H	4H 27.8	28.6	28.6	29.3	30.2	24.8	25.6	25.6	26.3	27.2
	6H 30.5	31.1	31.2	31.9	32.8	26.5	27.1	27.2	27.9	28.8
	8H 32.0	32.6	32.8	33.4	34.4	27.3	27.8	28.1	28.6	29.6
Variations with the observer position at spacings:										
S = 1.0H	+ 0.1 / - 0.1					+ 0.1 / - 0.1				
1.5H	+ 0.2 / - 0.2					+ 0.2 / - 0.3				
2.0H	+ 0.2 / - 0.3					+ 0.3 / - 0.4				

CIE Pub.117, 345.5 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -3.7)

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-07-10

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:24.00V I:0.3350A P:8.039W PF:1.000 Freq:0Hz Lamp Flux:345.539x1 lm		
NAME: NNR18	TYPE:	WEIGHT:
SPEC.:NNR18-9LWNW24CSN050CC0100	DIM.: 1000*18mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*18	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	43	30	23	42	30	23	40	29	22	15
0.80	52	38	30	50	37	29	47	36	28	20
1.00	59	46	37	57	44	36	53	45	35	25
1.25	66	53	43	64	51	42	59	48	41	30
1.50	71	58	49	69	56	47	63	53	45	34
2.00	79	67	57	76	64	56	69	60	53	40
2.50	84	72	63	80	70	61	73	64	58	44
3.00	88	77	69	84	74	66	76	68	62	47
4.00	93	84	76	88	80	73	80	74	68	52
5.00	96	88	81	92	84	78	83	77	72	55
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-07-10

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:24.00V I:0.3350A P:8.039W PF:1.000 Freq:0Hz Lamp Flux:345.539x1 lm		
NAME: NNR18	TYPE:	WEIGHT:
SPEC.:NNR18-9LWNW24CSN050CC0100	DIM.: 1000*18mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*18	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-07-10

Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

AAI Figure

Test:U:24.00V I:0.3350A P:8.039W PF:1.000 Freq:0Hz Lamp Flux:345.539x1 lm		
NAME: NNR18	TYPE:	WEIGHT:
SPEC.:NNR18-9LWNW24CSN050CC0100	DIM.: 1000*18mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*18	Shielding Angle:

Flux out:254.7 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-07-10

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:24.00V I:0.3350A P:8.039W PF:1.000 Freq:0Hz Lamp Flux:345.539x1 lm		
NAME: NNR18	TYPE:	WEIGHT:
SPEC.:NNR18-9LWNW24CSN050CC0100	DIM.: 1000*18mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*18	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-07-10

Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:24.00V I:0.3350A P:8.039W PF:1.000 Freq:0Hz Lamp Flux:345.539x1 lm		
NAME: NNR18	TYPE:	WEIGHT:
SPEC.:NNR18-9LWNW24CSN050CC0100	DIM.: 1000*18mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*18	Shielding Angle:


AvgL	cd/m2
L_0~180(65)av	7589
L_0~180(75)av	12142
L_0~180(85)av	34404
L_90~270(65)av	2331
L_90~270(75)av	2013
L_90~270(85)av	1490
L_45(65)av	5506
L_45(75)av	8382
L_45(85)av	22876

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-07-10

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: JYH
 Test Date: 2021-07-10

deg Range: 0 - 180DEG
 Interval: 1.0DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity: 65.0%
 Test Distance: 10.950m [K=1.0000]
 Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:24.00V I:0.3350A P:8.039W PF:1.000 Freq:0Hz Lamp Flux:345.539x1 lm		
NAME: NNR18	TYPE:	WEIGHT:
SPEC.:NNR18-9LWNW24CSN050CC0100	DIM.: 1000*18mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*18	Shielding Angle:

Table--1

UNIT: cd

C(DEG) g (DEG)	0	45	90	135	180	225	270	315										
0	52.6	52.2	51.9	52.0	52.6	52.2	51.9	52.0										
5	52.6	52.0	51.7	52.0	52.8	52.2	51.6	51.9										
10	52.9	51.8	51.0	52.0	53.5	52.3	50.9	51.7										
15	53.4	51.5	49.7	51.9	54.4	52.2	49.7	51.4										
20	53.9	51.1	48.0	51.8	55.3	52.0	48.0	50.9										
25	54.5	50.4	45.9	51.5	56.3	51.7	46.0	50.2										
30	55.0	49.5	43.3	51.0	57.3	51.2	43.5	49.3										
35	55.5	48.5	40.4	50.4	58.2	50.5	40.7	48.2										
40	56.0	47.2	37.2	49.7	59.0	49.7	37.3	47.0										
45	56.4	45.9	33.7	48.8	59.5	48.8	33.8	45.6										
50	56.5	44.6	30.0	47.7	59.9	47.6	30.1	44.2										
55	56.5	43.1	26.1	46.5	59.9	46.4	26.4	42.7										
60	56.3	41.7	21.9	45.2	59.9	45.1	22.0	41.2										
65	55.8	40.2	17.7	43.8	59.6	43.7	17.7	39.8										
70	55.3	38.8	13.5	42.4	59.2	42.3	13.5	38.4										
75	54.6	37.4	9.38	40.9	58.6	40.8	9.37	37.0										
80	53.6	36.1	5.54	39.4	57.6	39.2	5.56	35.6										
85	51.8	34.5	2.28	37.6	56.2	37.4	2.39	34.1										
90	50.0	32.4	0.49	35.8	54.6	35.5	0.42	32.5										
95	48.1	30.4	0.29	33.6	53.0	33.2	0.19	30.7										
100	44.2	27.0	0.24	28.8	48.8	28.4	0.21	24.5										
105	39.7	23.6	0.24	24.2	43.6	23.8	0.28	22.8										
110	35.0	19.8	0.29	19.7	38.3	19.4	0.34	18.7										
115	30.2	16.0	0.31	14.5	32.9	14.5	0.37	15.6										
120	25.4	12.0	0.41	10.5	27.5	10.8	0.42	12.7										
125	20.7	9.16	0.72	6.90	22.2	7.10	0.47	10.1										
130	16.1	6.82	0.54	3.59	17.0	3.67	0.50	7.62										
135	11.8	4.35	0.53	1.41	12.3	1.39	0.53	4.53										
140	7.84	2.40	0.60	0.81	7.50	0.84	0.57	3.04										
145	3.88	1.23	0.83	0.79	3.17	0.82	0.61	1.99										
150	1.65	0.75	0.70	0.79	0.87	0.81	0.64	1.38										
155	0.98	0.73	0.69	0.81	0.82	0.81	0.68	1.03										
160	0.94	0.73	0.73	0.82	0.75	0.81	0.74	0.78										
165	0.92	0.75	0.75	0.85	0.74	0.81	0.79	0.73										
170	0.82	0.80	0.83	0.88	0.73	0.82	0.84	0.74										
175	0.76	0.85	0.84	0.92	0.71	0.83	0.91	0.83										
180	0.75	0.85	0.90	0.92	0.74	0.85	0.92	0.90										

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-07-10

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks: