


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:24.00V I:0.3158A P:7.579W PF:1.000 Freq:0Hz Lamp Flux:945.857x1 lm		
NAME: D8802408NO	TYPE:	WEIGHT:
SPEC.:D8802408NO-9NWDA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 124.81 lm/W			
MODEL	D8802408NO	I _{max} (cd)	306.8	S/MH(C0/180)	1.31
NOMINAL POWER(W)	6.6	LOR(%)	100.0	S/MH(C90/270)	1.29
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	945.86	h UP,DN(C0-180)	0.9,49.5
NOMINAL FLUX(lm)	945.857	CIE CLASS	DIRECT	h UP,DN(C180-360)	0.8,48.8
LAMPS INSIDE	1	h up(%)	1.7	CIBSE SHR NOM	1.50
TEST VOLTAGE(V)	24	h down(%)	98.3	CIBSE SHR MAX	1.50



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-12-09

g Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	303.0	303.5	302.8	302.6	301.0	301.4	302.0	302.8	0- 10	29.07	29.07	3.07,3.07
20	290.8	291.5	290.1	289.5	287.1	287.5	288.8	289.7	10- 20	83.89	113.0	11.9,11.9
30	269.3	270.3	268.4	267.6	264.5	264.9	266.6	267.7	20- 30	128.9	241.8	25.6,25.6
40	238.7	239.9	237.9	236.8	233.3	233.8	235.8	236.7	30- 40	158.4	400.2	42.3,42.3
50	198.8	200.1	198.1	197.2	193.7	194.1	196.2	196.6	40- 50	168.0	568.2	60.1,60.1
60	150.2	151.7	149.6	149.4	146.2	146.7	148.4	148.2	50- 60	155.2	723.4	76.5,76.5
70	94.40	95.72	93.85	94.52	92.17	92.62	93.73	92.73	60- 70	120.4	843.8	89.2,89.2
80	37.34	38.25	36.62	38.02	37.13	37.38	37.72	36.25	70- 80	68.65	912.5	96.5,96.5
90	2.806	2.821	1.616	2.775	2.575	2.609	1.008	1.806	80- 90	17.69	930.2	98.3,98.3
100	1.189	1.244	1.169	1.210	0.8571	0.7940	0.7582	0.8117	90-100	1.195	931.4	98.5,98.5
110	1.802	1.812	1.669	1.819	1.752	1.509	1.585	1.467	100-110	1.389	932.8	98.6,98.6
120	2.662	2.619	2.563	2.605	2.573	2.203	2.238	2.308	110-120	2.067	934.8	98.8,98.8
130	3.352	3.233	3.172	3.194	3.254	2.798	2.746	2.845	120-130	2.493	937.3	99.1,99.1
140	3.847	3.654	3.594	3.647	3.795	3.386	3.133	3.159	130-140	2.559	939.9	99.4,99.4
150	4.168	3.894	3.927	4.102	4.122	3.961	3.522	3.306	140-150	2.324	942.2	99.6,99.6
160	4.541	4.108	4.448	4.582	4.449	4.462	4.302	3.707	150-160	1.885	944.1	99.8,99.8
170	4.796	4.683	5.083	4.997	4.362	4.889	5.024	4.574	160-170	1.288	945.4	99.9,99.9
180	4.696	5.457	5.544	5.571	4.696	5.450	5.584	5.571	170-180	0.4734	945.9	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-12-09

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:24.00V I:0.3158A P:7.579W PF:1.000 Freq:0Hz Lamp Flux:945.857x1 lm		
NAME: D8802408NO	TYPE:	WEIGHT:
SPEC.:D8802408NO-9NWDA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8	Shielding Angle:



LUMINANCE cd/(m2)		
G(180)	C0/180	C90/270
85	20911	19462
80	26878	26360
75	31492	31190
70	34501	34299
65	36398	36232
60	37552	37394
55	38271	38121
50	38655	38517
45	38870	38722


C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-12-09

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:24.00V I:0.3158A P:7.579W PF:1.000 Freq:0Hz Lamp Flux:945.857x1 lm		
NAME: D8802408NO	TYPE:	WEIGHT:
SPEC.:D8802408NO-9NWDA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8	Shielding Angle:

r _{cc}	80%			70%			50%			30%			10%			0
r _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Coefficients of Utilization(CU)												
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.10	1.10	1.10	1.05	1.05	1.05	1.01	1.01	1.01	.98
1.0	1.03	.99	.95	1.01	.97	.93	.96	.93	.90	.92	.89	.87	.88	.86	.84	.82
2.0	.90	.83	.77	.88	.81	.76	.84	.78	.74	.80	.76	.72	.77	.73	.70	.68
3.0	.78	.70	.64	.77	.69	.63	.74	.67	.62	.71	.65	.60	.68	.63	.59	.57
4.0	.69	.60	.54	.68	.60	.53	.65	.58	.52	.63	.56	.51	.60	.55	.50	.48
5.0	.62	.53	.46	.61	.52	.46	.58	.51	.45	.56	.49	.44	.54	.48	.44	.41
6.0	.55	.46	.40	.54	.46	.40	.52	.45	.39	.51	.44	.39	.49	.43	.38	.36
7.0	.50	.41	.35	.49	.41	.35	.48	.40	.35	.46	.39	.34	.45	.38	.34	.32
8.0	.46	.37	.31	.45	.37	.31	.43	.36	.31	.42	.35	.30	.41	.35	.30	.28
9.0	.42	.34	.28	.41	.33	.28	.40	.33	.28	.39	.32	.27	.38	.32	.27	.25
10.0	.39	.31	.25	.38	.30	.25	.37	.30	.25	.36	.29	.25	.35	.29	.25	.23



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-12-09

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:24.00V I:0.3158A P:7.579W PF:1.000 Freq:0Hz Lamp Flux:945.857x1 lm		
NAME: D8802408NO	TYPE:	WEIGHT:
SPEC.:D8802408NO-9NWDA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Wall Exitance Coefficients(WEC)												
0.0																
1.0	.314	.178	.057	.306	.175	.055	.292	.167	.053	.279	.161	.052	.267	.155	.050	
2.0	.295	.162	.050	.289	.159	.049	.276	.153	.048	.264	.148	.046	.254	.143	.045	
3.0	.273	.145	.044	.267	.143	.043	.256	.139	.042	.246	.135	.041	.236	.131	.040	
4.0	.252	.131	.038	.246	.129	.038	.237	.125	.037	.227	.122	.037	.219	.119	.036	
5.0	.233	.119	.034	.228	.117	.034	.219	.114	.034	.211	.111	.033	.203	.108	.033	
6.0	.215	.108	.031	.211	.107	.031	.203	.104	.030	.196	.102	.030	.189	.099	.030	
7.0	.200	.099	.028	.197	.098	.028	.189	.096	.028	.183	.094	.027	.177	.092	.027	
8.0	.187	.091	.026	.184	.090	.026	.177	.089	.025	.171	.087	.025	.166	.085	.025	
9.0	.175	.085	.024	.172	.084	.024	.166	.082	.023	.161	.081	.023	.156	.079	.023	
10.0	.165	.079	.022	.162	.078	.022	.157	.077	.022	.152	.075	.021	.147	.074	.021	

rcc	80%			70%			50%			30%			10%			0	
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
rfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)										
0.0	.203	.203	.203	.174	.174	.174	.118	.118	.118	.068	.068	.068	.022	.022	.022		
1.0	.193	.169	.147	.165	.145	.126	.113	.100	.087	.065	.058	.051	.021	.019	.016		
2.0	.186	.145	.110	.159	.125	.095	.109	.086	.067	.063	.050	.039	.020	.016	.013		
3.0	.178	.127	.087	.153	.110	.075	.105	.076	.053	.060	.045	.031	.019	.014	.010		
4.0	.170	.114	.071	.146	.098	.062	.101	.069	.043	.058	.040	.026	.019	.013	.008		
5.0	.163	.104	.060	.140	.090	.052	.096	.063	.037	.056	.037	.022	.018	.012	.007		
6.0	.156	.095	.052	.134	.083	.045	.092	.058	.032	.054	.034	.019	.017	.011	.006		
7.0	.149	.088	.046	.128	.077	.040	.089	.054	.028	.051	.032	.017	.017	.010	.006		
8.0	.143	.083	.042	.123	.072	.036	.085	.050	.026	.049	.030	.015	.016	.010	.005		
9.0	.136	.078	.038	.118	.068	.033	.081	.047	.024	.047	.028	.014	.015	.009	.005		
10.0	.131	.074	.035	.113	.064	.031	.078	.045	.022	.046	.027	.013	.015	.009	.004		

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-12-09

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:24.00V I:0.3158A P:7.579W PF:1.000 Freq:0Hz Lamp Flux:945.857x1 lm											
NAME: D8802408NO						TYPE:		WEIGHT:			
SPEC.:D8802408NO-9NWNDA012WC0100						DIM.: 1000*8*1.5mm		SERIAL No.:			
MFR.: COLORS						SUR.:1000*8		Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	25.8	27.3	26.1	27.5	27.8	25.8	27.3	26.1	27.5	27.8	
	3H	27.4	28.8	27.7	29.0	29.3	27.3	28.7	27.7	29.0	29.3
	4H	28.0	29.3	28.3	29.6	29.9	27.9	29.3	28.3	29.5	29.8
	6H	28.4	29.6	28.7	29.9	30.2	28.3	29.6	28.7	29.9	30.2
	8H	28.5	29.7	28.8	30.0	30.3	28.4	29.6	28.8	29.9	30.3
	12H	28.5	29.7	28.9	30.0	30.3	28.5	29.6	28.8	29.9	30.3
4H	2H	26.4	27.8	26.8	28.0	28.3	26.4	27.7	26.8	28.0	28.3
	3H	28.2	29.3	28.5	29.7	30.0	28.2	29.3	28.5	29.6	30.0
	4H	28.9	30.0	29.3	30.3	30.7	28.9	29.9	29.3	30.3	30.7
	6H	29.4	30.3	29.8	30.7	31.1	29.4	30.3	29.8	30.7	31.1
	8H	29.6	30.4	30.0	30.8	31.3	29.5	30.4	30.0	30.8	31.2
	12H	29.6	30.4	30.1	30.9	31.3	29.6	30.4	30.0	30.8	31.3
8H	4H	29.1	30.0	29.6	30.4	30.8	29.1	30.0	29.6	30.4	30.8
	6H	29.8	30.5	30.3	31.0	31.4	29.8	30.5	30.2	30.9	31.4
	8H	30.0	30.7	30.5	31.1	31.6	30.0	30.6	30.5	31.1	31.6
	12H	30.2	30.7	30.7	31.2	31.7	30.1	30.7	30.6	31.2	31.7
12H	4H	29.2	30.0	29.6	30.4	30.8	29.1	29.9	29.6	30.4	30.8
	6H	29.8	30.5	30.3	30.9	31.4	29.8	30.5	30.3	30.9	31.4
	8H	30.1	30.7	30.6	31.1	31.7	30.1	30.6	30.6	31.1	31.6
Variations with the observer position at spacings:											
S = 1.0H	+ 0.1 / - 0.2					+ 0.1 / - 0.2					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					
2.0H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					

CIE Pub.117, 945.9 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -0.2)

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-12-09

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:24.00V I:0.3158A P:7.579W PF:1.000 Freq:0Hz Lamp Flux:945.857x1 lm		
NAME: D8802408NO	TYPE:	WEIGHT:
SPEC.:D8802408NO-9NWDA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	56	44	37	55	44	37	54	44	37	30
0.80	66	54	47	65	54	47	63	53	46	39
1.00	75	63	56	73	63	56	71	64	55	48
1.25	82	71	64	80	70	63	77	69	62	55
1.50	87	77	70	85	76	69	82	74	68	60
2.00	94	85	79	92	84	78	88	81	76	68
2.50	98	90	84	96	89	83	92	86	81	72
3.00	101	94	89	99	93	88	95	90	85	76
4.00	106	100	95	103	98	93	98	94	91	81
5.00	108	103	99	105	101	97	101	97	94	84
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-12-09

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:24.00V I:0.3158A P:7.579W PF:1.000 Freq:0Hz Lamp Flux:945.857x1 lm		
NAME: D8802408NO	TYPE:	WEIGHT:
SPEC.:D8802408NO-9NWDA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-12-09

Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

AAI Figure

Test:U:24.00V I:0.3158A P:7.579W PF:1.000 Freq:0Hz Lamp Flux:945.857x1 lm		
NAME: D8802408NO	TYPE:	WEIGHT:
SPEC.:D8802408NO-9NWDA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8	Shielding Angle:

Flux out:723.4 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-12-09

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


Test:U:24.00V I:0.3158A P:7.579W PF:1.000 Freq:0Hz Lamp Flux:945.857x1 lm		
NAME: D8802408NO	TYPE:	WEIGHT:
SPEC.:D8802408NO-9NWDA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8	Shielding Angle:



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-12-09

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2020-12-09

Range: 0 - 180DEG
Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:24.00V I:0.3158A P:7.579W PF:1.000 Freq:0Hz Lamp Flux:945.857x1 lm		
NAME: D8802408NO	TYPE:	WEIGHT:
SPEC.:D8802408NO-9NWDA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8	Shielding Angle:

Table--1

UNIT: cd

C(DEG) g (DEG)	0	45	90	135	180	225	270	315										
0	306	307	307	307	306	307	307	307										
5	306	306	306	306	305	305	305	306										
10	303	304	303	303	301	301	302	303										
15	298	299	298	297	295	296	297	297										
20	291	292	290	289	287	288	289	290										
25	281	282	280	280	277	277	279	280										
30	269	270	268	268	264	265	267	268										
35	255	256	254	253	250	250	252	253										
40	239	240	238	237	233	234	236	237										
45	220	221	219	218	214	215	217	218										
50	199	200	198	197	194	194	196	197										
55	176	177	175	174	171	171	173	173										
60	150	152	150	149	146	147	148	148										
65	123	124	122	123	120	120	122	121										
70	94.4	95.7	93.8	94.5	92.2	92.6	93.7	92.7										
75	65.2	66.4	64.6	65.7	64.1	64.4	65.2	63.9										
80	37.3	38.3	36.6	38.0	37.1	37.4	37.7	36.3										
85	14.6	14.7	13.6	14.9	14.7	14.9	14.5	13.5										
90	2.81	2.82	1.62	2.77	2.57	2.61	1.01	1.81										
95	1.22	1.31	1.19	1.25	0.73	0.65	0.40	0.65										
100	1.19	1.24	1.17	1.21	0.86	0.79	0.76	0.81										
105	1.40	1.46	1.27	1.46	1.31	1.15	1.21	1.13										
110	1.80	1.81	1.67	1.82	1.75	1.51	1.58	1.47										
115	2.22	2.23	2.14	2.23	2.16	1.87	1.93	1.91										
120	2.66	2.62	2.56	2.61	2.57	2.20	2.24	2.31										
125	3.01	2.96	2.88	2.91	2.93	2.50	2.51	2.67										
130	3.35	3.23	3.17	3.19	3.25	2.80	2.75	2.84										
135	3.62	3.47	3.39	3.44	3.54	3.09	2.95	3.04										
140	3.85	3.65	3.59	3.65	3.79	3.39	3.13	3.16										
145	4.03	3.79	3.77	3.87	3.98	3.69	3.28	3.25										
150	4.17	3.89	3.93	4.10	4.12	3.96	3.52	3.31										
155	4.35	3.99	4.15	4.36	4.30	4.23	3.87	3.43										
160	4.54	4.11	4.45	4.58	4.45	4.46	4.30	3.71										
165	4.70	4.32	4.78	4.78	4.58	4.67	4.67	4.11										
170	4.80	4.68	5.08	5.00	4.36	4.89	5.02	4.57										
175	4.62	5.11	5.33	5.29	4.32	5.14	5.35	5.10										
180	4.70	5.46	5.54	5.57	4.70	5.45	5.58	5.57										

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-12-09

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks: