


## LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:24.00V I:0.2979A P:7.149W PF:1.000 Freq:0Hz Lamp Flux:522.91lx1 lm		
NAME: NTT0606	TYPE:	WEIGHT:
SPEC.:NTT0606-9NW24CSN050CC0100	DIM.: 1000*06*06mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*06	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 73.14 lm/W			
MODEL	NMT0606	I <sub>max</sub> (cd)	176.4	S/MH(C0/180)	1.26
NOMINAL POWER(W)	7.2	LOR(%)	100.0	S/MH(C90/270)	1.24
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	522.91	h UP,DN(C0-180)	1.2,49.6
NOMINAL FLUX(lm)	522.911	CIE CLASS	DIRECT	h UP,DN(C180-360)	1.0,48.2
LAMPS INSIDE	1	h up(%)	2.2	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	24	h down(%)	97.8	CIBSE SHR MAX	1.35



C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2021-02-01

Range: 0 - 180DEG  
Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

## ZONAL FLUX DIAGRAM

### ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	173.4	173.9	173.4	173.2	173.4	172.4	172.1	172.6	0- 10	16.67	16.67	3.19,3.19
20	164.3	165.1	164.2	164.1	164.3	162.4	161.8	162.9	10- 20	47.72	64.39	12.3,12.3
30	149.7	150.7	149.3	149.5	149.8	146.8	145.9	147.6	20- 30	72.26	136.7	26.1,26.1
40	130.4	131.3	129.5	130.1	130.6	126.7	125.3	127.6	30- 40	87.15	223.8	42.8,42.8
50	107.0	108.0	105.8	106.7	107.5	102.9	101.1	103.8	40- 50	90.67	314.5	60.1,60.1
60	80.53	81.49	79.06	80.29	81.32	76.44	74.10	77.25	50- 60	82.57	397.0	75.9,75.9
70	51.93	52.72	49.95	51.68	53.13	47.98	45.23	48.68	60- 70	63.93	461.0	88.2,88.2
80	24.27	24.12	20.47	23.26	25.43	20.45	16.98	20.99	70- 80	37.76	498.7	95.4,95.4
90	7.551	5.625	0.9848	4.653	6.771	3.540	0.4884	4.459	80- 90	12.54	511.3	97.8,97.8
100	4.005	2.390	0.5477	1.561	2.424	1.298	0.4084	1.691	90-100	2.902	514.2	98.3,98.3
110	2.160	1.176	0.7480	1.036	1.382	0.8550	0.8551	1.062	100-110	1.465	515.7	98.6,98.6
120	1.663	1.416	1.208	1.417	1.390	1.169	1.210	1.289	110-120	1.210	516.9	98.8,98.8
130	1.897	1.717	1.549	1.743	1.764	1.502	1.503	1.610	120-130	1.346	518.2	99.1,99.1
140	2.211	1.944	1.797	1.997	2.064	1.843	1.744	1.810	130-140	1.393	519.6	99.4,99.4
150	2.444	2.071	2.017	2.278	2.264	2.223	1.944	1.904	140-150	1.277	520.9	99.6,99.6
160	2.565	2.218	2.430	2.585	2.478	2.491	2.378	2.144	150-160	1.047	521.9	99.8,99.8
170	2.699	2.612	2.792	2.832	2.465	2.772	2.786	2.558	160-170	0.7206	522.6	99.9,99.9
180	2.598	3.079	3.099	3.079	2.605	3.079	3.113	3.086	170-180	0.2653	522.9	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG  
 C Interval: 45.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:JYH  
 Test Date:2021-02-01

g Range: 0 - 180DEG  
 Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
 Humidity:65.0%  
 Test Distance:10.950m [K=1.0000]  
 Remarks:

### LUMINANCE LIMITATION CURVES

Test:U:24.00V I:0.2979A P:7.149W PF:1.000 Freq:0Hz Lamp Flux:522.91lx1 lm		
NAME: NTT0606	TYPE:	WEIGHT:
SPEC.:NTT0606-9NW24CSN050CC0100	DIM.: 1000*06*06mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*06	Shielding Angle:



LUMINANCE cd/(m2)		
G( DEG)	C0/180	C90/270
85	2640	1526
80	2329	1965
75	2420	2251
70	2530	2434
65	2618	2552
60	2684	2635
55	2733	2695
50	2774	2744
45	2807	2783


C Range: 0 - 360DEG  
 C Interval: 45.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:JYH  
 Test Date:2021-02-01

g Range: 0 - 180DEG  
 g Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
 Humidity:65.0%  
 Test Distance:10.950m [K=1.0000]  
 Remarks:

## CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:24.00V I:0.2979A P:7.149W PF:1.000 Freq:0Hz Lamp Flux:522.91lx1 lm		
NAME: NTT0606	TYPE:	WEIGHT:
SPEC.:NTT0606-9NW24CSN050CC0100	DIM.: 1000*06*06mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*06	Shielding Angle:

r <sub>cc</sub>	80%			70%			50%			30%			10%			0
r <sub>w</sub>	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r <sub>fc</sub>	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio															



C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2021-02-01

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

WEC AND CCEC

Test:U:24.00V I:0.2979A P:7.149W PF:1.000 Freq:0Hz Lamp Flux:522.91lx1 lm		
NAME: NTT0606	TYPE:	WEIGHT:
SPEC.:NTT0606-9NW24CSN050CC0100	DIM.: 1000*06*06mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*06	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)									
0.0																
1.0	.317	.180	.057	.309	.176	.056	.295	.169	.054	.281	.162	.052	.269	.156	.050	
2.0	.296	.162	.050	.289	.159	.049	.276	.153	.048	.264	.148	.046	.253	.143	.045	
3.0	.272	.145	.043	.266	.143	.043	.255	.138	.042	.244	.134	.041	.234	.130	.040	
4.0	.251	.130	.038	.245	.128	.038	.235	.125	.037	.226	.121	.037	.217	.118	.036	
5.0	.231	.118	.034	.227	.116	.034	.217	.113	.033	.209	.110	.033	.201	.107	.032	
6.0	.214	.107	.031	.210	.106	.031	.202	.103	.030	.194	.101	.030	.187	.099	.029	
7.0	.199	.099	.028	.195	.097	.028	.188	.095	.027	.181	.093	.027	.175	.091	.027	
8.0	.186	.091	.026	.183	.090	.025	.176	.088	.025	.170	.086	.025	.164	.084	.025	
9.0	.174	.084	.024	.171	.083	.023	.165	.082	.023	.160	.080	.023	.154	.078	.023	
10.0	.164	.079	.022	.161	.078	.022	.156	.076	.021	.150	.075	.021	.146	.073	.021	

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Ceiling Cavity Exitance Coefficients(CCEC)												
0.0	.207	.207	.207	.177	.177	.177	.121	.121	.121	.070	.070	.070	.022	.022	.022	
1.0	.198	.173	.151	.169	.149	.130	.116	.102	.090	.067	.059	.052	.021	.019	.017	
2.0	.190	.149	.115	.163	.128	.099	.111	.089	.069	.064	.052	.041	.021	.017	.013	
3.0	.182	.132	.091	.156	.114	.079	.107	.079	.055	.062	.046	.033	.020	.015	.011	
4.0	.175	.118	.075	.150	.102	.066	.103	.071	.046	.060	.042	.027	.019	.014	.009	
5.0	.167	.108	.064	.144	.093	.056	.099	.065	.040	.057	.038	.023	.018	.013	.008	
6.0	.160	.100	.057	.138	.086	.049	.095	.060	.035	.055	.036	.021	.018	.012	.007	
7.0	.153	.093	.051	.132	.081	.044	.091	.056	.031	.053	.033	.019	.017	.011	.006	
8.0	.147	.087	.046	.126	.076	.040	.087	.053	.029	.051	.031	.017	.016	.010	.006	
9.0	.141	.082	.043	.121	.071	.037	.084	.050	.026	.049	.030	.016	.016	.010	.005	
10.0	.135	.078	.040	.116	.068	.035	.081	.048	.025	.047	.028	.015	.015	.009	.005	

C Range: 0 - 360DEG  
 C Interval: 45.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:JYH  
 Test Date:2021-02-01

g Range: 0 - 180DEG  
 g Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
 Humidity:65.0%  
 Test Distance:10.950m [K=1.0000]  
 Remarks:

UGR(Unified Glare Rating) Table

Test:U:24.00V I:0.2979A P:7.149W PF:1.000 Freq:0Hz Lamp Flux:522.91lx1 lm											
NAME: NTT0606					TYPE:			WEIGHT:			
SPEC.:NTT0606-9NW24CSN050CC0100					DIM.: 1000*06*06mm			SERIAL No.:01			
MFR.: COLORS					SUR.:1000*06			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise				Viewed endwise					
x = 2H y = 2H	18.6	20.1	18.9	20.3	20.6	18.5	20.0	18.8	20.3	20.5	
	3H	20.2	21.6	20.5	21.9	22.2	20.1	21.5	20.4	21.8	22.0
	4H	20.9	22.2	21.2	22.5	22.8	20.7	22.0	21.1	22.3	22.6
	6H	21.4	22.6	21.8	22.9	23.3	21.1	22.4	21.5	22.7	23.0
	8H	21.6	22.8	22.0	23.1	23.5	21.3	22.5	21.6	22.8	23.1
	12H	21.8	22.9	22.1	23.3	23.6	21.3	22.5	21.7	22.8	23.2
4H	2H	19.2	20.6	19.6	20.8	21.2	19.2	20.5	19.5	20.8	21.1
	3H	21.0	22.2	21.4	22.5	22.9	20.9	22.1	21.3	22.4	22.8
	4H	21.8	22.9	22.2	23.2	23.6	21.7	22.7	22.1	23.1	23.5
	6H	22.5	23.4	22.9	23.8	24.2	22.2	23.2	22.7	23.6	24.0
	8H	22.7	23.6	23.2	24.0	24.5	22.4	23.3	22.9	23.7	24.1
	12H	23.0	23.8	23.4	24.2	24.7	22.5	23.3	23.0	23.7	24.2
8H	4H	22.1	23.0	22.6	23.4	23.8	22.0	22.9	22.4	23.3	23.7
	6H	22.9	23.7	23.4	24.1	24.6	22.7	23.4	23.2	23.9	24.4
	8H	23.3	24.0	23.8	24.4	24.9	23.0	23.6	23.5	24.1	24.6
	12H	23.7	24.2	24.2	24.7	25.2	23.2	23.7	23.7	24.2	24.7
12H	4H	22.1	22.9	22.6	23.4	23.8	22.0	22.8	22.5	23.2	23.7
	6H	23.0	23.7	23.5	24.1	24.6	22.8	23.4	23.3	23.9	24.4
	8H	23.4	24.0	23.9	24.5	25.0	23.1	23.7	23.6	24.2	24.7
Variations with the observer position at spacings:											
S = 1.0H	+ 0.1 / - 0.2				+ 0.1 / - 0.2						
1.5H	+ 0.2 / - 0.3				+ 0.2 / - 0.3						
2.0H	+ 0.1 / - 0.3				+ 0.1 / - 0.3						

CIE Pub.117, 522.9 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -2.3)

C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2021-02-01

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

## UTILIZATION FACTORS TABLE

Test:U:24.00V I:0.2979A P:7.149W PF:1.000 Freq:0Hz Lamp Flux:522.91lx1 lm		
NAME: NTT0606	TYPE:	WEIGHT:
SPEC.:NTT0606-9NW24CSN050CC0100	DIM.: 1000*06*06mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*06	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	56	45	38	56	44	38	54	44	37	31
0.80	66	55	47	65	54	47	63	53	47	39
1.00	75	63	56	73	63	56	71	64	55	48
1.25	82	71	64	80	70	63	77	69	62	55
1.50	87	77	70	85	76	69	82	74	68	60
2.00	94	85	78	92	84	77	88	81	76	67
2.50	98	90	83	95	88	82	91	85	80	72
3.00	101	94	88	99	92	87	94	89	85	76
4.00	105	99	94	103	97	93	98	94	90	80
5.00	108	103	98	105	101	97	100	97	93	83
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2021-02-01

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

### ISOCANDELA DIAGRAM

Test:U:24.00V I:0.2979A P:7.149W PF:1.000 Freq:0Hz Lamp Flux:522.91lx1 lm		
NAME: NTT0606	TYPE:	WEIGHT:
SPEC.:NTT0606-9NW24CSN050CC0100	DIM.: 1000*06*06mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*06	Shielding Angle:



C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2021-02-01


Range: 0 - 180DEG  
Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:



## AAI Figure

Test:U:24.00V I:0.2979A P:7.149W PF:1.000 Freq:0Hz Lamp Flux:522.91lx1 lm		
NAME: NTT0606	TYPE:	WEIGHT:
SPEC.:NTT0606-9NW24CSN050CC0100	DIM.: 1000*06*06mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*06	Shielding Angle:

Flux out:365.7 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2021-02-01

g Range: 0 - 180DEG  
Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

### ISOLUX DIAGRAM

Test:U:24.00V I:0.2979A P:7.149W PF:1.000 Freq:0Hz Lamp Flux:522.91lx1 lm		
NAME: NTT0606	TYPE:	WEIGHT:
SPEC.:NTT0606-9NW24CSN050CC0100	DIM.: 1000*06*06mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*06	Shielding Angle:



C Range: 0 - 360DEG  
 C Interval: 45.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:JYH  
 Test Date:2021-02-01

g Range: 0 - 180DEG  
 g Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
 Humidity:65.0%  
 Test Distance:10.950m [K=1.0000]  
 Remarks:

### LED Avg.L Report

Test:U:24.00V I:0.2979A P:7.149W PF:1.000 Freq:0Hz Lamp Flux:522.91lx1 lm		
NAME: NTT0606	TYPE:	WEIGHT:
SPEC.:NTT0606-9NW24CSN050CC0100	DIM.: 1000*06*06mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*06	Shielding Angle:


AvgL	cd/m2
L_0~180(65)av	2637
L_0~180(75)av	2462
L_0~180(85)av	2669
L_90~270(65)av	2456
L_90~270(75)av	2114
L_90~270(85)av	1291
L_45(65)av	2553
L_45(75)av	2306
L_45(85)av	2109

Standard: GB/T 29293-2012

C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2021-02-01

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

### Planar Illuminance Curve



C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators: JYH  
Test Date: 2021-02-01

deg Range: 0 - 180DEG  
deg Interval: 1.0DEG  
Test System: EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity: 65.0%  
Test Distance: 10.950m [K=1.0000]  
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:24.00V I:0.2979A P:7.149W PF:1.000 Freq:0Hz Lamp Flux:522.91lx1 lm		
NAME: NTT0606	TYPE:	WEIGHT:
SPEC.:NTT0606-9NW24CSN050CC0100	DIM.: 1000*06*06mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*06	Shielding Angle:

Table--1

UNIT: cd

C(DEG) g (DEG)	0	45	90	135	180	225	270	315										
0	176	176	176	176	176	176	176	176										
5	176	176	176	175	176	175	175	175										
10	173	174	173	173	173	172	172	173										
15	170	170	170	169	170	168	168	168										
20	164	165	164	164	164	162	162	163										
25	158	159	157	157	158	155	154	156										
30	150	151	149	150	150	147	146	148										
35	141	142	140	140	141	137	136	138										
40	130	131	130	130	131	127	125	128										
45	119	120	118	119	120	115	114	116										
50	107	108	106	107	108	103	101	104										
55	94.1	95.0	92.8	93.8	94.8	90.0	87.9	90.9										
60	80.5	81.5	79.1	80.3	81.3	76.4	74.1	77.3										
65	66.4	67.3	64.7	66.2	67.4	62.3	59.8	63.1										
70	51.9	52.7	49.9	51.7	53.1	48.0	45.2	48.7										
75	37.6	38.1	35.0	37.2	38.9	33.7	30.7	34.3										
80	24.3	24.1	20.5	23.3	25.4	20.4	17.0	21.0										
85	13.8	12.5	7.98	11.7	14.1	9.60	5.53	10.3										
90	7.55	5.63	0.98	4.65	6.77	3.54	0.49	4.46										
95	5.06	3.31	0.58	2.19	3.50	1.75	0.71	2.82										
100	4.01	2.39	0.55	1.56	2.42	1.30	0.41	1.69										
105	2.97	1.50	0.55	1.04	1.95	0.90	0.64	1.22										
110	2.16	1.18	0.75	1.04	1.38	0.85	0.86	1.06										
115	1.75	1.21	0.99	1.22	1.30	0.98	1.04	1.08										
120	1.66	1.42	1.21	1.42	1.39	1.17	1.21	1.29										
125	1.72	1.58	1.37	1.58	1.58	1.34	1.36	1.48										
130	1.90	1.72	1.55	1.74	1.76	1.50	1.50	1.61										
135	2.04	1.85	1.68	1.87	1.92	1.69	1.62	1.73										
140	2.21	1.94	1.80	2.00	2.06	1.84	1.74	1.81										
145	2.33	2.02	1.90	2.14	2.17	2.01	1.84	1.89										
150	2.44	2.07	2.02	2.28	2.26	2.22	1.94	1.90										
155	2.50	2.14	2.21	2.45	2.39	2.35	2.12	2.00										
160	2.56	2.22	2.43	2.59	2.48	2.49	2.38	2.14										
165	2.66	2.40	2.63	2.70	2.56	2.64	2.59	2.35										
170	2.70	2.61	2.79	2.83	2.46	2.77	2.79	2.56										
175	2.60	2.86	2.98	2.99	2.45	2.87	2.98	2.87										
180	2.60	3.08	3.10	3.08	2.60	3.08	3.11	3.09										

C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2021-02-01

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks: