


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:48.00V I:0.1800A P:8.640W PF:1.000 Freq:49.99Hz Lamp Flux:829.372x1 lm		
NAME: TLS-R25FPXBS500-H20NW8X-DC	TYPE:	WEIGHT:
SPEC.: TLS-R25FPXBS500-H20NW8X-DC	DIM.: 500*25*25mm	SERIAL No.:
MFR.: COLORS	SUR.:500*25mm	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 95.99 lm/W			
MODEL	TLS-R25FPXBS500	Imax(cd)	413.1	S/MH(C0/180)	1.01
NOMINAL POWER(W)	10	LOR(%)	100.0	S/MH(C90/270)	1.17
RATED VOLTAGE(V)	48	TOTAL FLUX(lm)	829.37	h UP,DN(C0-180)	0.8,48.2
NOMINAL FLUX(lm)	829.372	CIE CLASS	DIRECT	h UP,DN(C180-360)	0.7,50.3
LAMPS INSIDE	1	h up(%)	1.6	CIBSE SHR NOM	1.00
TEST VOLTAGE(V)	48	h down(%)	98.4	CIBSE SHR MAX	1.15



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-15

Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	394.0	394.9	397.8	393.9	390.9	397.8	402.1	400.5	0- 10	38.56	38.56	4.65,4.65
20	342.9	353.5	364.6	353.3	350.2	359.1	371.2	359.4	10- 20	106.6	145.2	17.5,17.5
30	257.2	288.4	311.3	304.3	290.6	309.3	321.2	293.0	20- 30	151.3	296.4	35.7,35.7
40	177.5	208.1	241.7	229.3	204.4	234.0	252.3	209.1	30- 40	161.8	458.3	55.3,55.3
50	121.3	137.6	167.0	155.0	138.6	157.0	174.8	138.6	40- 50	140.6	598.9	72.2,72.2
60	71.89	85.50	103.8	98.00	86.00	98.93	107.0	85.79	50- 60	106.7	705.6	85.1,85.1
70	34.16	43.19	55.85	54.59	47.17	54.81	58.06	42.87	60- 70	68.56	774.2	93.3,93.3
80	9.895	14.85	21.74	20.72	16.71	20.67	23.15	14.61	70- 80	34.24	808.4	97.5,97.5
90	0.4280	0.5618	0.7077	0.7131	0.0867	0.2221	0.6286	0.1345	80- 90	8.036	816.4	98.4,98.4
100	0.4708	0.6417	0.6793	0.5744	0.2548	0.2931	0.4548	0.3939	90-100	0.4320	816.9	98.5,98.5
110	0.8815	1.069	0.9742	0.8504	0.6548	0.6729	1.104	0.9265	100-110	0.6832	817.5	98.6,98.6
120	1.509	1.785	1.994	1.464	1.237	1.155	2.092	1.675	110-120	1.225	818.8	98.7,98.7
130	2.344	2.747	3.086	2.192	1.885	1.783	3.235	2.656	120-130	1.825	820.6	98.9,98.9
140	3.305	3.888	3.987	3.146	2.640	2.651	4.223	3.910	130-140	2.294	822.9	99.2,99.2
150	4.380	4.516	4.468	4.110	3.587	3.637	4.849	4.883	140-150	2.446	825.3	99.5,99.5
160	5.123	4.681	4.669	4.950	4.523	4.595	5.034	5.324	150-160	2.127	827.5	99.8,99.8
170	5.512	4.643	5.103	5.377	4.880	4.896	5.097	5.488	160-170	1.420	828.9	99.9,99.9
180	4.896	5.551	6.172	6.199	4.902	5.551	6.179	6.192	170-180	0.4986	829.4	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-09-15

g Range: 0 - 180DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:48.00V I:0.1800A P:8.640W PF:1.000 Freq:49.99Hz Lamp Flux:829.372x1 lm		
NAME: TLS-R25FPXBS500-H20NW8X-DC	TYPE:	WEIGHT:
SPEC.: TLS-R25FPXBS500-H20NW8X-DC	DIM.: 500*25*25mm	SERIAL No.:
MFR.: COLORS	SUR.: 500*25mm	Shielding Angle:



LUMINANCE cd/(m2)		
G(180)	C0/180	C90/270
85	1694	8384
80	4559	10016
75	6444	11553
70	7989	13064
65	9390	14701
60	11503	16612
55	13427	18660
50	15101	20787
45	16751	23010


C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: JYH
 Test Date: 2020-09-15

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity: 65.0%
 Test Distance: 10.950m [K=1.0000]
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:48.00V I:0.1800A P:8.640W PF:1.000 Freq:49.99Hz Lamp Flux:829.372x1 lm		
NAME: TLS-R25FPXB500-H20NW8X-DC	TYPE:	WEIGHT:
SPEC.: TLS-R25FPXB500-H20NW8X-DC	DIM.: 500*25*25mm	SERIAL No.:
MFR.: COLORS	SUR.:500*25mm	Shielding Angle:

r _{cc}	80%			70%			50%			30%			10%			0
r _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Coefficients of Utilization(CU)												
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.10	1.10	1.10	1.05	1.05	1.05	1.01	1.01	1.01	.98
1.0	1.06	1.02	.99	1.03	.90	.97	.99	.96	.94	.95	.93	.90	.91	.89	.88	.85
2.0	.94	.88	.83	.92	.86	.82	.88	.84	.80	.85	.81	.78	.82	.78	.76	.74
3.0	.84	.76	.71	.82	.75	.70	.79	.73	.68	.76	.71	.67	.73	.69	.66	.64
4.0	.75	.67	.61	.74	.66	.61	.71	.65	.60	.69	.63	.59	.66	.62	.58	.56
5.0	.68	.60	.54	.67	.59	.53	.65	.58	.53	.62	.57	.52	.61	.55	.51	.49
6.0	.62	.54	.48	.61	.53	.47	.59	.52	.47	.57	.51	.46	.55	.50	.46	.44
7.0	.56	.48	.43	.56	.48	.42	.54	.47	.42	.52	.46	.42	.51	.46	.41	.39
8.0	.52	.44	.39	.51	.44	.38	.50	.43	.38	.48	.42	.38	.47	.42	.37	.36
9.0	.48	.40	.35	.47	.40	.35	.46	.39	.35	.45	.39	.34	.44	.38	.34	.32
10.0	.44	.37	.32	.44	.37	.32	.43	.36	.32	.42	.36	.32	.41	.35	.31	.30



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-15

g Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:48.00V I:0.1800A P:8.640W PF:1.000 Freq:49.99Hz Lamp Flux:829.372x1 lm		
NAME: TLS-R25FPXBS500-H20NW8X-DC	TYPE:	WEIGHT:
SPEC.:TLS-R25FPXBS500-H20NW8X-DC	DIM.: 500*25*25mm	SERIAL No.:
MFR.: COLORS	SUR.:500*25mm	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)									
0.0																
1.0	.268	.152	.048	.260	.148	.047	.246	.141	.045	.233	.135	.043	.222	.128	.041	
2.0	.256	.140	.043	.249	.137	.042	.237	.132	.041	.226	.127	.040	.215	.122	.038	
3.0	.240	.128	.038	.234	.125	.038	.223	.121	.037	.213	.117	.036	.204	.113	.035	
4.0	.224	.116	.034	.219	.114	.034	.209	.111	.033	.200	.108	.032	.192	.104	.032	
5.0	.209	.106	.031	.204	.105	.031	.196	.102	.030	.188	.099	.030	.181	.097	.029	
6.0	.195	.098	.028	.191	.097	.028	.184	.094	.027	.177	.092	.027	.170	.090	.027	
7.0	.183	.091	.026	.180	.089	.025	.173	.087	.025	.166	.085	.025	.160	.083	.025	
8.0	.172	.084	.024	.169	.083	.024	.163	.081	.023	.157	.080	.023	.152	.078	.023	
9.0	.162	.078	.022	.159	.078	.022	.154	.076	.022	.149	.075	.021	.144	.073	.021	
10.0	.153	.073	.020	.151	.073	.020	.146	.071	.020	.141	.070	.020	.136	.069	.020	

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Ceiling Cavity Exitance Coefficients(CCEC)												
0.0	.202	.202	.202	.173	.173	.173	.118	.118	.118	.068	.068	.068	.022	.022	.022	
1.0	.189	.169	.150	.162	.145	.129	.111	.099	.089	.064	.058	.052	.020	.019	.017	
2.0	.179	.144	.114	.154	.124	.099	.105	.086	.069	.061	.050	.040	.019	.016	.013	
3.0	.171	.126	.091	.146	.109	.079	.101	.076	.055	.058	.044	.033	.019	.014	.011	
4.0	.163	.113	.074	.140	.097	.065	.096	.068	.045	.056	.040	.027	.018	.013	.009	
5.0	.155	.102	.063	.133	.088	.054	.092	.062	.038	.053	.036	.023	.017	.012	.008	
6.0	.148	.093	.054	.127	.081	.047	.088	.057	.033	.051	.033	.020	.016	.011	.007	
7.0	.142	.086	.048	.122	.075	.042	.084	.053	.029	.049	.031	.018	.016	.010	.006	
8.0	.136	.081	.043	.117	.070	.037	.081	.049	.026	.047	.029	.016	.015	.009	.005	
9.0	.130	.076	.039	.112	.066	.034	.078	.046	.024	.045	.027	.014	.015	.009	.005	
10.0	.125	.071	.036	.107	.062	.031	.075	.044	.022	.043	.026	.013	.014	.008	.004	

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-15

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:48.00V I:0.1800A P:8.640W PF:1.000 Freq:49.99Hz Lamp Flux:829.372x1 lm											
NAME: TLS-R25FPXBS500-H20NW8X-DC						TYPE:		WEIGHT:			
SPEC.:TLS-R25FPXBS500-H20NW8X-DC						DIM.: 500*25*25mm		SERIAL No.:			
MFR.: COLORS						SUR.:500*25mm		Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	21.5	22.9	21.8	23.1	23.3	22.9	24.2	23.2	24.5	24.7	
	3H	22.3	23.5	22.6	23.7	24.0	23.9	25.2	24.2	25.4	
	4H	22.5	23.7	22.8	23.9	24.2	24.3	25.5	24.6	25.8	
	6H	22.6	23.7	22.9	24.0	24.3	24.6	25.7	24.9	26.0	
	8H	22.6	23.6	22.9	23.9	24.2	24.7	25.7	25.0	26.0	
	12H	22.5	23.5	22.9	23.9	24.2	24.7	25.7	25.1	26.0	
4H	2H	22.0	23.2	22.3	23.5	23.8	23.1	24.3	23.5	24.6	
	3H	22.9	23.9	23.3	24.3	24.6	24.3	25.4	24.7	25.7	
	4H	23.2	24.2	23.6	24.5	24.9	24.8	25.8	25.2	26.1	
	6H	23.4	24.2	23.8	24.6	25.0	25.2	26.0	25.6	26.4	
	8H	23.4	24.2	23.9	24.6	25.0	25.3	26.1	25.8	26.5	
	12H	23.4	24.1	23.8	24.5	24.9	25.4	26.1	25.9	26.5	
8H	4H	23.4	24.2	23.8	24.6	25.0	24.9	25.7	25.3	26.0	
	6H	23.7	24.3	24.1	24.7	25.2	25.4	26.0	25.8	26.4	
	8H	23.7	24.3	24.2	24.7	25.2	25.6	26.1	26.0	26.6	
	12H	23.7	24.2	24.2	24.7	25.2	25.7	26.2	26.2	26.6	
12H	4H	23.4	24.1	23.9	24.5	25.0	24.9	25.6	25.3	26.0	
	6H	23.7	24.3	24.2	24.7	25.2	25.4	25.9	25.8	26.4	
	8H	23.8	24.3	24.3	24.7	25.2	25.6	26.0	26.1	26.5	
Variations with the observer position at spacings:											
S = 1.0H	+ 0.4 / - 0.5					+ 0.2 / - 0.3					
1.5H	+ 0.2 / - 0.4					+ 0.2 / - 0.3					
2.0H	+ 0.5 / - 0.9					+ 0.6 / - 0.7					

CIE Pub.117, 829.4 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -0.7)

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-15

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:48.00V I:0.1800A P:8.640W PF:1.000 Freq:49.99Hz Lamp Flux:829.372x1 lm		
NAME: TLS-R25FPXBS500-H20NW8X-DC	TYPE:	WEIGHT:
SPEC.:TLS-R25FPXBS500-H20NW8X-DC	DIM.: 500*25*25mm	SERIAL No.:
MFR.: COLORS	SUR.:500*25mm	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	64	53	47	63	53	47	62	52	47	41
0.80	74	63	57	73	63	57	71	62	56	50
1.00	81	72	65	80	71	65	78	72	64	58
1.25	88	79	73	87	78	72	84	77	71	65
1.50	92	84	78	91	83	77	88	81	76	69
2.00	98	91	86	97	90	85	93	87	83	76
2.50	102	95	90	100	94	89	96	91	87	79
3.00	105	99	94	102	97	93	98	94	90	82
4.00	108	103	99	106	101	98	101	98	95	86
5.00	110	106	102	108	104	101	103	100	97	88
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-09-15

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:48.00V I:0.1800A P:8.640W PF:1.000 Freq:49.99Hz Lamp Flux:829.372x1 lm		
NAME: TLS-R25FPXBS500-H20NW8X-DC	TYPE:	WEIGHT:
SPEC.: TLS-R25FPXBS500-H20NW8X-DC	DIM.: 500*25*25mm	SERIAL No.:
MFR.: COLORS	SUR.:500*25mm	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-15

Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

AAI Figure

Test:U:48.00V I:0.1800A P:8.640W PF:1.000 Freq:49.99Hz Lamp Flux:829.372x1 lm		
NAME: TLS-R25FPXBS500-H20NW8X-DC	TYPE:	WEIGHT:
SPEC.: TLS-R25FPXBS500-H20NW8X-DC	DIM.: 500*25*25mm	SERIAL No.:
MFR.: COLORS	SUR.:500*25mm	Shielding Angle:

Flux out:426.9 lm




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2020-09-15

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


Test:U:48.00V I:0.1800A P:8.640W PF:1.000 Freq:49.99Hz Lamp Flux:829.372x1 lm		
NAME: TLS-R25FPXBS500-H20NW8X-DC	TYPE:	WEIGHT:
SPEC.: TLS-R25FPXBS500-H20NW8X-DC	DIM.: 500*25*25mm	SERIAL No.:
MFR.: COLORS	SUR.:500*25mm	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2020-09-15

Range: 0 - 180DEG
Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2020-09-15

Range: 0 - 180DEG
Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:48.00V I:0.1800A P:8.640W PF:1.000 Freq:49.99Hz Lamp Flux:829.372x1 lm		
NAME: TLS-R25FPXBS500-H20NW8X-DC	TYPE:	WEIGHT:
SPEC.: TLS-R25FPXBS500-H20NW8X-DC	DIM.: 500*25*25mm	SERIAL No.:
MFR.: COLORS	SUR.:500*25mm	Shielding Angle:

Table--1

UNIT: cd

C(DEG) g (DEG)	0	45	90	135	180	225	270	315										
0	412	411	411	412	412	411	411	412										
5	407	407	407	407	407	407	410	410										
10	394	395	398	394	391	398	402	400										
15	373	377	384	376	372	381	388	383										
20	343	353	365	353	350	359	371	359										
25	303	323	340	328	330	333	349	328										
30	257	288	311	304	291	309	321	293										
35	213	248	279	276	242	281	289	252										
40	178	208	242	229	204	234	252	209										
45	148	169	203	189	170	191	213	170										
50	121	138	167	155	139	157	175	139										
55	96.3	110	134	125	110	126	139	111										
60	71.9	85.5	104	98.0	86.0	98.9	107	85.8										
65	49.6	63.6	77.7	74.6	65.5	75.2	80.3	63.7										
70	34.2	43.2	55.9	54.6	47.2	54.8	58.1	42.9										
75	20.8	27.4	37.4	36.9	30.4	36.9	39.2	27.3										
80	9.89	14.8	21.7	20.7	16.7	20.7	23.1	14.6										
85	1.85	4.74	9.13	8.51	6.19	8.08	9.98	4.45										
90	0.43	0.56	0.71	0.71	0.09	0.22	0.63	0.13										
95	0.42	0.55	0.69	0.64	0.12	0.16	0.27	0.19										
100	0.47	0.64	0.68	0.57	0.25	0.29	0.45	0.39										
105	0.61	0.80	0.71	0.65	0.45	0.46	0.74	0.63										
110	0.88	1.07	0.97	0.85	0.65	0.67	1.10	0.93										
115	1.17	1.42	1.45	1.14	0.91	0.93	1.56	1.25										
120	1.51	1.79	1.99	1.46	1.24	1.16	2.09	1.68										
125	1.89	2.22	2.54	1.81	1.56	1.43	2.69	2.13										
130	2.34	2.75	3.09	2.19	1.89	1.78	3.24	2.66										
135	2.84	3.30	3.58	2.66	2.23	2.14	3.77	3.28										
140	3.31	3.89	3.99	3.15	2.64	2.65	4.22	3.91										
145	3.81	4.30	4.27	3.64	3.09	3.14	4.62	4.50										
150	4.38	4.52	4.47	4.11	3.59	3.64	4.85	4.88										
155	4.78	4.65	4.60	4.54	4.07	4.15	5.02	5.12										
160	5.12	4.68	4.67	4.95	4.52	4.60	5.03	5.32										
165	5.51	4.66	4.71	5.21	4.91	4.78	5.05	5.45										
170	5.51	4.64	5.10	5.38	4.88	4.90	5.10	5.49										
175	4.84	4.94	5.72	5.73	4.59	5.10	5.58	5.58										
180	4.90	5.55	6.17	6.20	4.90	5.55	6.18	6.19										

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-15

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks: