


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:48.00V I:0.1880A P:9.000W PF:1.000 Freq:49.99Hz Lamp Flux:974.56x1 lm		
NAME: TLS-R25LSFBS500-H20N8X-DC	TYPE:	WEIGHT:
SPEC.: TLS-R25LSFBS500-H20N8X-DC	DIM.: 500*25*25mm	SERIAL No.:
MFR.: COLORS	SUR.:500*25mm	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 108.28 lm/W			
MODEL	TLS-R25LSFBS500	Imax(cd)	451.6	S/MH(C0/180)	1.28
NOMINAL POWER(W)	10	LOR(%)	100.0	S/MH(C90/270)	1.23
RATED VOLTAGE(V)	48	TOTAL FLUX(lm)	974.56	h UP,DN(C0-180)	0.8,48.3
NOMINAL FLUX(lm)	974.56	CIE CLASS	DIRECT	h UP,DN(C180-360)	0.8,50.1
LAMPS INSIDE	1	h up(%)	1.6	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	48	h down(%)	98.4	CIBSE SHR MAX	1.35



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-15

Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	402.4	377.1	354.8	371.9	395.9	370.4	351.2	396.9	0- 10	35.24	35.24	3.62,3.62
20	451.6	412.9	334.9	403.3	432.9	400.6	328.9	430.8	10- 20	111.2	146.5	15,15
30	375.3	405.3	301.5	388.4	368.4	381.3	295.4	399.1	20- 30	178.8	325.3	33.4,33.4
40	246.5	312.0	254.0	314.0	279.6	306.0	249.4	291.5	30- 40	203.4	528.7	54.2,54.2
50	127.2	189.5	193.0	215.2	210.6	210.4	188.2	172.8	40- 50	180.4	709.0	72.8,72.8
60	57.60	96.13	122.8	133.8	141.1	130.5	118.7	90.06	50- 60	132.2	841.3	86.3,86.3
70	16.61	38.96	63.23	71.99	62.35	70.27	59.74	36.95	60- 70	79.95	921.2	94.5,94.5
80	3.240	8.183	24.19	16.42	8.367	14.99	22.42	7.388	70- 80	31.81	953.0	97.8,97.8
90	0.4080	0.6075	1.215	1.448	0.3272	0.3362	0.9521	0.5484	80- 90	5.992	959.0	98.4,98.4
100	0.3920	0.6430	0.7348	0.6701	0.3410	0.2803	0.5214	0.4872	90-100	0.5570	959.6	98.5,98.5
110	1.354	1.403	1.055	0.8836	0.5157	0.7060	1.317	1.240	100-110	0.7712	960.4	98.5,98.5
120	2.409	2.411	2.302	1.638	1.123	1.427	2.567	2.291	110-120	1.496	961.9	98.7,98.7
130	3.377	3.690	3.553	2.806	2.146	2.518	3.743	3.684	120-130	2.316	964.2	98.9,98.9
140	4.434	5.057	4.361	4.224	3.629	3.806	4.422	5.140	130-140	2.927	967.1	99.2,99.2
150	5.495	5.758	4.709	5.324	5.012	4.809	4.569	5.750	140-150	3.028	970.1	99.5,99.5
160	6.164	5.443	4.800	5.585	5.555	5.170	4.588	5.519	150-160	2.463	972.6	99.8,99.8
170	5.500	4.803	4.909	5.414	5.196	4.930	4.710	4.963	160-170	1.486	974.1	100,100
180	4.809	5.230	5.758	5.784	4.796	5.203	5.771	5.778	170-180	0.4821	974.6	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-09-15

g Range: 0 - 180DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:48.00V I:0.1880A P:9.000W PF:1.000 Freq:49.99Hz Lamp Flux:974.56x1 lm		
NAME: TLS-R25LSFBS500-H20N8X-DC	TYPE:	WEIGHT:
SPEC.: TLS-R25LSFBS500-H20NW8X-DC	DIM.: 500*25*25mm	SERIAL No.:
MFR.: COLORS	SUR.:500*25mm	Shielding Angle:



LUMINANCE cd/(m2)		
G(DEG)	C0/180	C90/270
85	558	10147
80	1492	11144
75	2731	12792
70	3885	14790
65	6433	17164
60	9217	19652
55	12164	22019
50	15834	24023
45	20470	25486


C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-09-15

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:48.00V I:0.1880A P:9.000W PF:1.000 Freq:49.99Hz Lamp Flux:974.56x1 lm		
NAME: TLS-R25LSFBS500-H20N8X-DC	TYPE:	WEIGHT:
SPEC.: TLS-R25LSFBS500-H20NW8X-DC	DIM.: 500*25*25mm	SERIAL No.:
MFR.: COLORS	SUR.:500*25mm	Shielding Angle:

r _{cc}	80%			70%			50%			30%			10%			0
r _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Coefficients of Utilization(CU)															
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.10	1.10	1.10	1.05	1.05	1.05	1.01	1.01	1.01	.98
1.0	1.06	1.02	.99	1.04	1.00	.97	.99	.96	.94	.95	.93	.91	.91	.89	.88	.86
2.0	.94	.88	.83	.92	.87	.82	.88	.84	.80	.85	.81	.78	.82	.79	.76	.74
3.0	.84	.76	.71	.82	.75	.70	.79	.73	.68	.76	.71	.67	.73	.69	.66	.64
4.0	.75	.67	.61	.74	.66	.60	.71	.64	.59	.68	.63	.58	.66	.61	.58	.55
5.0	.67	.59	.53	.66	.59	.53	.64	.57	.52	.62	.56	.51	.60	.55	.51	.49
6.0	.61	.53	.47	.60	.52	.47	.58	.51	.46	.56	.50	.46	.55	.49	.45	.43
7.0	.56	.47	.42	.55	.47	.41	.53	.46	.41	.52	.45	.41	.50	.45	.40	.38
8.0	.51	.43	.37	.50	.43	.37	.49	.42	.37	.47	.41	.37	.46	.41	.36	.35
9.0	.47	.39	.34	.46	.39	.34	.45	.38	.33	.44	.38	.33	.43	.37	.33	.31
10.0	.43	.36	.31	.43	.36	.31	.42	.35	.30	.41	.35	.30	.40	.34	.30	.28



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-15

g Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:48.00V I:0.1880A P:9.000W PF:1.000 Freq:49.99Hz Lamp Flux:974.56x1 lm		
NAME: TLS-R25LSFBS500-H20N8X-DC	TYPE:	WEIGHT:
SPEC.:TLS-R25LSFBS500-H20NW8X-DC	DIM.: 500*25*25mm	SERIAL No.:
MFR.: COLORS	SUR.:500*25mm	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Wall Exitance Coefficients(WEC)															
0.0																
1.0	.263	.150	.047	.256	.146	.046	.242	.139	.044	.229	.132	.042	.217	.126	.041	
2.0	.254	.139	.043	.248	.136	.042	.235	.131	.041	.224	.126	.039	.214	.121	.038	
3.0	.240	.128	.038	.234	.125	.038	.223	.121	.037	.213	.117	.036	.204	.113	.035	
4.0	.225	.117	.034	.220	.115	.034	.210	.112	.033	.201	.108	.033	.193	.105	.032	
5.0	.211	.107	.031	.206	.106	.031	.198	.103	.030	.190	.100	.030	.182	.097	.029	
6.0	.197	.099	.028	.193	.098	.028	.186	.095	.028	.179	.093	.027	.172	.091	.027	
7.0	.185	.092	.026	.182	.091	.026	.175	.088	.025	.169	.086	.025	.163	.084	.025	
8.0	.174	.085	.024	.171	.084	.024	.165	.082	.024	.159	.081	.023	.154	.079	.023	
9.0	.164	.080	.022	.162	.079	.022	.156	.077	.022	.151	.076	.022	.146	.074	.021	
10.0	.155	.075	.021	.153	.074	.021	.148	.072	.020	.143	.071	.020	.139	.070	.020	

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Ceiling Cavity Exitance Coefficients(CCEC)															
0.0	.203	.203	.203	.173	.173	.173	.118	.118	.118	.068	.068	.068	.022	.022	.022	
1.0	.189	.169	.150	.162	.145	.129	.111	.100	.089	.064	.058	.052	.020	.019	.017	
2.0	.180	.144	.115	.154	.124	.099	.105	.086	.069	.061	.050	.041	.019	.016	.013	
3.0	.171	.126	.091	.147	.109	.079	.101	.076	.055	.058	.044	.033	.019	.014	.011	
4.0	.163	.113	.074	.140	.098	.065	.096	.068	.045	.056	.040	.027	.018	.013	.009	
5.0	.156	.102	.063	.134	.088	.054	.092	.062	.038	.053	.036	.023	.017	.012	.008	
6.0	.149	.094	.054	.128	.081	.047	.089	.057	.033	.051	.033	.020	.017	.011	.007	
7.0	.143	.087	.048	.123	.075	.041	.085	.053	.029	.049	.031	.017	.016	.010	.006	
8.0	.137	.081	.043	.118	.070	.037	.082	.049	.026	.047	.029	.016	.015	.010	.005	
9.0	.131	.076	.039	.113	.066	.034	.078	.046	.024	.046	.027	.014	.015	.009	.005	
10.0	.126	.072	.036	.109	.062	.031	.075	.044	.022	.044	.026	.013	.014	.009	.004	

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-09-15

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

UGR(Unified Glare Rating) Table

Test:U:48.00V I:0.1880A P:9.000W PF:1.000 Freq:49.99Hz Lamp Flux:974.56x1 lm										
NAME: TLS-R25LSFBS500-H20N8X-DC					TYPE:			WEIGHT:		
SPEC.:TLS-R25LSFBS500-H20NW8X-DC					DIM.: 500*25*25mm			SERIAL No.:		
MFR.: COLORS					SUR.:500*25mm			Shielding Angle:		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	21.4	22.8	21.7	23.0	23.2	23.1	24.4	23.3	24.6	24.9
	3H	21.6	22.8	21.9	23.1	23.3	23.9	25.2	24.2	25.4
	4H	21.5	22.7	21.9	23.0	23.3	24.2	25.4	24.5	25.7
	6H	21.5	22.6	21.8	22.9	23.2	24.4	25.5	24.8	25.8
	8H	21.4	22.5	21.8	22.8	23.1	24.5	25.6	24.9	25.9
	12H	21.4	22.4	21.7	22.7	23.0	24.5	25.6	24.9	25.9
4H	2H	21.8	23.0	22.1	23.3	23.5	23.2	24.4	23.5	24.6
	3H	22.1	23.1	22.4	23.4	23.7	24.2	25.2	24.5	25.5
	4H	22.1	23.0	22.5	23.4	23.7	24.6	25.5	24.9	25.8
	6H	22.0	22.9	22.5	23.2	23.6	24.9	25.7	25.3	26.1
	8H	22.0	22.8	22.4	23.1	23.6	25.0	25.7	25.4	26.1
	12H	21.9	22.6	22.4	23.1	23.5	25.0	25.7	25.5	26.2
8H	4H	22.1	22.9	22.6	23.3	23.7	24.5	25.3	24.9	25.6
	6H	22.1	22.8	22.6	23.2	23.6	24.9	25.5	25.3	25.9
	8H	22.1	22.6	22.6	23.1	23.6	25.0	25.6	25.5	26.0
	12H	22.1	22.5	22.6	23.0	23.5	25.1	25.6	25.6	26.1
12H	4H	22.1	22.8	22.6	23.2	23.7	24.5	25.2	24.9	25.6
	6H	22.1	22.7	22.6	23.1	23.6	24.8	25.4	25.3	25.8
	8H	22.1	22.6	22.6	23.0	23.5	25.0	25.5	25.5	25.9
Variations with the observer position at spacings:										
S = 1.0H	+ 1.1 / - 1.5					+ 0.5 / - 0.4				
1.5H	+ 0.5 / - 1.3					+ 0.2 / - 0.4				
2.0H	+ 1.4 / - 2.4					+ 0.8 / - 1.0				

CIE Pub.117, 974.6 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -0.1)

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-15

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:48.00V I:0.1880A P:9.000W PF:1.000 Freq:49.99Hz Lamp Flux:974.56x1 lm		
NAME: TLS-R25LSFBS500-H20N8X-DC	TYPE:	WEIGHT:
SPEC.:TLS-R25LSFBS500-H20NW8X-DC	DIM.: 500*25*25mm	SERIAL No.:
MFR.: COLORS	SUR.:500*25mm	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	63	52	46	62	52	46	61	52	46	40
0.80	73	63	56	72	62	56	70	61	55	49
1.00	81	71	65	80	71	65	78	72	64	58
1.25	88	79	73	86	78	72	84	77	71	65
1.50	93	84	78	91	83	77	88	81	76	69
2.00	99	91	86	97	90	85	93	88	83	76
2.50	102	95	90	100	94	89	96	91	87	79
3.00	105	99	94	103	97	93	98	94	91	82
4.00	108	103	99	106	101	98	101	98	95	86
5.00	110	106	103	108	104	101	103	100	98	88
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-09-15

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:48.00V I:0.1880A P:9.000W PF:1.000 Freq:49.99Hz Lamp Flux:974.56x1 lm		
NAME: TLS-R25LSFBS500-H20N8X-DC	TYPE:	WEIGHT:
SPEC.: TLS-R25LSFBS500-H20NW8X-DC	DIM.: 500*25*25mm	SERIAL No.:
MFR.: COLORS	SUR.: 500*25mm	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2020-09-15

deg Range: 0 - 180DEG
Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

AAI Figure

Test:U:48.00V I:0.1880A P:9.000W PF:1.000 Freq:49.99Hz Lamp Flux:974.56x1 lm		
NAME: TLS-R25LSFBS500-H20N8X-DC	TYPE:	WEIGHT:
SPEC.: TLS-R25LSFBS500-H20NW8X-DC	DIM.: 500*25*25mm	SERIAL No.:
MFR.: COLORS	SUR.:500*25mm	Shielding Angle:

Flux out:724.6 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-15

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


Test:U:48.00V I:0.1880A P:9.000W PF:1.000 Freq:49.99Hz Lamp Flux:974.56x1 lm		
NAME: TLS-R25LSFBS500-H20N8X-DC	TYPE:	WEIGHT:
SPEC.: TLS-R25LSFBS500-H20NW8X-DC	DIM.: 500*25*25mm	SERIAL No.:
MFR.: COLORS	SUR.:500*25mm	Shielding Angle:



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: JYH
 Test Date: 2020-09-15

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity: 65.0%
 Test Distance: 10.950m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: JYH
 Test Date: 2020-09-15

Range: 0 - 180DEG
 Interval: 1.0DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity: 65.0%
 Test Distance: 10.950m [K=1.0000]
 Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:48.00V I:0.1880A P:9.000W PF:1.000 Freq:49.99Hz Lamp Flux:974.56x1 lm		
NAME: TLS-R25LSFBS500-H20N8X-DC	TYPE:	WEIGHT:
SPEC.: TLS-R25LSFBS500-H20NW8X-DC	DIM.: 500*25*25mm	SERIAL No.:
MFR.: COLORS	SUR.:500*25mm	Shielding Angle:

Table--1

UNIT: cd

C(DEC) g (DEC)	0	45	90	135	180	225	270	315										
0	358	356	360	366	358	356	360	366										
5	373	363	359	363	365	358	358	379										
10	402	377	355	372	396	370	351	397										
15	437	395	347	388	428	388	341	417										
20	452	413	335	403	433	401	329	431										
25	428	421	320	406	408	400	314	427										
30	375	405	302	388	368	381	295	399										
35	312	367	280	357	324	349	274	351										
40	246	312	254	314	280	306	249	292										
45	181	250	225	265	241	258	220	230										
50	127	190	193	215	211	210	188	173										
55	87.2	138	158	171	179	166	154	127										
60	57.6	96.1	123	134	141	131	119	90.1										
65	34.0	64.1	90.7	101	107	99.2	86.6	61.0										
70	16.6	39.0	63.2	72.0	62.4	70.3	59.7	37.0										
75	8.83	19.3	41.4	41.8	21.7	40.9	38.6	17.6										
80	3.24	8.18	24.2	16.4	8.37	15.0	22.4	7.39										
85	0.61	1.15	11.1	6.35	3.74	4.73	10.1	1.03										
90	0.41	0.61	1.22	1.45	0.33	0.34	0.95	0.55										
95	0.38	0.53	0.74	0.93	0.33	0.25	0.33	0.41										
100	0.39	0.64	0.73	0.67	0.34	0.28	0.52	0.49										
105	0.72	0.98	0.75	0.66	0.38	0.45	0.86	0.86										
110	1.35	1.40	1.05	0.88	0.52	0.71	1.32	1.24										
115	1.88	1.86	1.63	1.22	0.78	1.03	1.89	1.71										
120	2.41	2.41	2.30	1.64	1.12	1.43	2.57	2.29										
125	2.94	3.02	2.96	2.16	1.57	1.91	3.19	2.94										
130	3.38	3.69	3.55	2.81	2.15	2.52	3.74	3.68										
135	3.88	4.40	4.02	3.51	2.85	3.16	4.15	4.44										
140	4.43	5.06	4.36	4.22	3.63	3.81	4.42	5.14										
145	4.98	5.54	4.58	4.86	4.38	4.37	4.55	5.62										
150	5.50	5.76	4.71	5.32	5.01	4.81	4.57	5.75										
155	5.96	5.68	4.79	5.61	5.49	5.12	4.59	5.74										
160	6.16	5.44	4.80	5.58	5.56	5.17	4.59	5.52										
165	6.10	5.11	4.82	5.54	5.52	5.11	4.56	5.20										
170	5.50	4.80	4.91	5.41	5.20	4.93	4.71	4.96										
175	4.79	4.87	5.34	5.46	4.60	4.96	5.22	5.10										
180	4.81	5.23	5.76	5.78	4.80	5.20	5.77	5.78										

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-15

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks: