


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:48.00V I:0.1100A P:5.280W PF:1.000 Freq:49.99Hz Lamp Flux:549.03x1 lm		
NAME: TLS-R35SXXBS35WA-T6NW9X-DC	TYPE:	WEIGHT:
SPEC.: TLS-R35SXXBS35WA-T6NW9X-DC	DIM.: 500*25*25mm	SERIAL No.:
MFR.: COLORS	SUR.:500*25mm	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 103.98 lm/W			
MODEL	TLS-R35SXXBS35WA	I _{max} (cd)	2699	S/MH(C0/180)	0.33
NOMINAL POWER(W)	6	LOR(%)	100.0	S/MH(C90/270)	0.38
RATED VOLTAGE(V)	48	TOTAL FLUX(lm)	549.03	h UP,DN(C0-180)	0.9,50.0
NOMINAL FLUX(lm)	549.03	CIE CLASS	DIRECT	h UP,DN(C180-360)	0.7,48.5
LAMPS INSIDE	1	h up(%)	1.6	CIBSE SHR NOM	0.00
TEST VOLTAGE(V)	48	h down(%)	98.4	CIBSE SHR MAX	1.00



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-15

Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	1275	1568	1910	2191	2242	1962	1616	1295	0- 10	208.6	208.6	38,38
20	167.5	234.4	374.7	565.7	561.6	331.9	202.5	146.1	10- 20	248.4	457.0	83.2,83.2
30	40.51	53.53	69.32	81.59	54.83	44.85	36.12	29.03	20- 30	58.29	515.3	93.9,93.9
40	8.871	12.90	18.03	22.00	16.06	12.60	9.831	7.480	30- 40	17.69	533.0	97.1,97.1
50	2.521	3.443	4.356	4.819	3.991	3.329	2.671	2.147	40- 50	5.331	538.3	98.1,98.1
60	0.3290	0.5915	1.124	1.262	0.9555	0.6563	0.4802	0.2547	50- 60	1.664	540.0	98.4,98.4
70	0.0870	0.0804	0.2011	0.1911	0.0867	0.1202	0.0065	0.0671	60- 70	0.2806	540.3	98.4,98.4
80	0.0004	0	0.0401	0	0	0.0200	0	0.0067	70- 80	0.0432	540.3	98.4,98.4
90	0	0	0	0	0	0	0	0	80- 90	0.0019	540.3	98.4,98.4
100	0	0	0	0	0	0	0	0	90-100	0	540.3	98.4,98.4
110	0	0	0	0	0	0	0	0	100-110	0	540.3	98.4,98.4
120	0	0.0267	0	0.0134	0.0070	0	0.0267	0	110-120	0.0020	540.3	98.4,98.4
130	0.1130	0.1276	0.0131	0.0802	0.0735	0.0200	0.1139	0.0935	120-130	0.0305	540.4	98.4,98.4
140	0.7054	0.5953	0.3937	0.3417	0.3073	0.3468	0.5547	0.6268	130-140	0.1869	540.5	98.5,98.5
150	2.507	2.039	1.469	1.231	1.070	1.195	1.661	2.178	140-150	0.5926	541.1	98.6,98.6
160	13.99	10.25	6.221	4.739	4.164	5.184	7.502	12.16	150-160	1.719	542.9	98.9,98.9
170	30.29	32.08	25.26	19.05	16.96	14.16	14.38	19.43	160-170	4.222	547.1	99.6,99.6
180	19.52	20.19	19.39	17.95	19.50	20.16	19.36	17.93	170-180	1.958	549.0	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-09-15

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:48.00V I:0.1100A P:5.280W PF:1.000 Freq:49.99Hz Lamp Flux:549.03x1 lm		
NAME: TLS-R35SXXBS35WA-T6NW9X-DC	TYPE:	WEIGHT:
SPEC.: TLS-R35SXXBS35WA-T6NW9X-DC	DIM.: 500*25*25mm	SERIAL No.:
MFR.: COLORS	SUR.: 500*25mm	Shielding Angle:



LUMINANCE cd/(m2)		
G(180)	C0/180	C90/270
85	0	0
80	0	18
75	12	29
70	20	47
65	33	60
60	53	180
55	151	350
50	314	542
45	500	904


C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: JYH
 Test Date: 2020-09-15

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity: 65.0%
 Test Distance: 10.950m [K=1.0000]
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:48.00V I:0.1100A P:5.280W PF:1.000 Freq:49.99Hz Lamp Flux:549.03x1 lm		
NAME: TLS-R35SXXBS35WA-T6NW9X-DC	TYPE:	WEIGHT:
SPEC.: TLS-R35SXXBS35WA-T6NW9X-DC	DIM.: 500*25*25mm	SERIAL No.:
MFR.: COLORS	SUR.:500*25mm	Shielding Angle:

r _{cc}	80%			70%			50%			30%			10%			0
r _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Coefficients of Utilization(CU)															
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.10	1.10	1.10	1.05	1.05	1.05	1.01	1.01	1.01	.98
1.0	1.13	1.11	1.09	1.10	1.09	1.07	1.06	1.05	1.04	1.02	1.01	1.00	.99	.98	.97	.95
2.0	1.07	1.05	1.02	1.06	1.03	1.01	1.02	1.00	.98	.99	.98	.96	.96	.95	.94	.92
3.0	1.03	.90	.97	1.02	.98	.96	.99	.96	.94	.96	.94	.93	.94	.92	.91	.90
4.0	.99	.95	.92	.98	.94	.92	.96	.93	.91	.94	.91	.89	.92	.90	.88	.87
5.0	.96	.92	.89	.95	.91	.88	.93	.90	.87	.91	.89	.87	.90	.88	.86	.85
6.0	.93	.89	.86	.92	.88	.85	.90	.87	.85	.89	.86	.84	.88	.85	.83	.82
7.0	.90	.86	.83	.89	.85	.83	.88	.85	.82	.87	.84	.82	.86	.83	.81	.80
8.0	.87	.83	.80	.87	.83	.80	.86	.82	.80	.85	.82	.79	.84	.81	.79	.78
9.0	.85	.81	.78	.84	.81	.78	.83	.80	.78	.83	.80	.77	.82	.79	.77	.76
10.0	.83	.79	.76	.82	.79	.76	.81	.78	.76	.81	.78	.76	.80	.77	.75	.74



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-09-15

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

WEC AND CCEC

Test:U:48.00V I:0.1100A P:5.280W PF:1.000 Freq:49.99Hz Lamp Flux:549.03x1 lm		
NAME: TLS-R35SXXBS35WA-T6NW9X-DC	TYPE:	WEIGHT:
SPEC.:TLS-R35SXXBS35WA-T6NW9X-DC	DIM.: 500*25*25mm	SERIAL No.:
MFR.: COLORS	SUR.:500*25mm	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Wall Exitance Coefficients(WEC)															
0.0																
1.0	.135	.077	.024	.128	.073	.023	.114	.066	.021	.102	.059	.019	.091	.053	.017	
2.0	.124	.068	.021	.119	.065	.020	.108	.060	.019	.097	.055	.017	.088	.050	.016	
3.0	.116	.062	.018	.111	.059	.018	.102	.055	.017	.093	.051	.016	.085	.047	.015	
4.0	.108	.056	.017	.104	.054	.016	.096	.051	.015	.089	.048	.014	.082	.045	.014	
5.0	.102	.052	.015	.098	.050	.015	.091	.048	.014	.085	.045	.013	.079	.042	.013	
6.0	.096	.048	.014	.093	.047	.014	.087	.045	.013	.082	.042	.012	.077	.040	.012	
7.0	.091	.045	.013	.088	.044	.013	.083	.042	.012	.078	.040	.012	.074	.038	.011	
8.0	.087	.042	.012	.084	.042	.012	.080	.040	.011	.076	.038	.011	.072	.037	.011	
9.0	.083	.040	.011	.081	.039	.011	.077	.038	.011	.073	.037	.010	.069	.035	.010	
10.0	.079	.038	.011	.077	.037	.010	.074	.036	.010	.070	.035	.010	.067	.034	.010	

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Ceiling Cavity Exitance Coefficients(CCEC)															
0.0	.203	.203	.203	.173	.173	.173	.118	.118	.118	.068	.068	.068	.022	.022	.022	
1.0	.180	.170	.160	.154	.146	.138	.106	.100	.095	.061	.058	.056	.019	.019	.018	
2.0	.162	.145	.131	.139	.125	.113	.095	.086	.079	.055	.050	.046	.018	.016	.015	
3.0	.147	.126	.108	.126	.108	.094	.087	.075	.066	.050	.044	.039	.016	.014	.013	
4.0	.134	.110	.092	.115	.095	.080	.079	.066	.056	.046	.039	.033	.015	.013	.011	
5.0	.124	.098	.079	.106	.085	.068	.073	.059	.048	.042	.035	.029	.014	.011	.009	
6.0	.115	.088	.069	.099	.076	.060	.068	.053	.042	.040	.031	.025	.013	.010	.008	
7.0	.107	.080	.060	.092	.069	.053	.064	.048	.037	.037	.029	.022	.012	.009	.007	
8.0	.101	.073	.054	.087	.063	.047	.060	.044	.033	.035	.026	.020	.011	.009	.007	
9.0	.095	.067	.049	.082	.058	.042	.057	.041	.030	.033	.024	.018	.011	.008	.006	
10.0	.090	.062	.044	.078	.054	.039	.054	.038	.027	.031	.023	.016	.010	.007	.005	

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-15

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:48.00V I:0.1100A P:5.280W PF:1.000 Freq:49.99Hz Lamp Flux:549.03x1 lm										
NAME: TLS-R35SXXBS35WA-T6NW9X-DC						TYPE:		WEIGHT:		
SPEC.:TLS-R35SXXBS35WA-T6NW9X-DC						DIM.: 500*25*25mm		SERIAL No.:		
MFR.: COLORS						SUR.:500*25mm		Shielding Angle:		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise				Viewed endwise				
x = 2H y = 2H	1.8	2.4	2.0	2.6	2.7	4.4	5.0	4.6	5.2	5.3
	3H	1.6	2.2	1.9	2.4	2.6	4.2	4.8	4.5	5.0
	4H	1.5	2.1	1.8	2.3	2.6	4.1	4.7	4.4	4.9
	6H	1.5	2.0	1.8	2.2	2.5	4.0	4.6	4.4	4.8
	8H	1.4	1.9	1.7	2.2	2.5	4.0	4.5	4.3	4.8
	12H	1.4	1.8	1.7	2.1	2.4	4.0	4.4	4.3	4.7
4H	2H	1.6	2.1	1.9	2.4	2.6	4.1	4.7	4.4	4.9
	3H	1.4	1.9	1.7	2.2	2.5	4.0	4.5	4.3	4.7
	4H	1.3	1.7	1.7	2.1	2.4	3.9	4.3	4.2	4.6
	6H	1.2	1.6	1.6	1.9	2.3	3.8	4.2	4.2	4.5
	8H	1.1	1.5	1.5	1.9	2.3	3.7	4.1	4.1	4.5
	12H	1.1	1.4	1.5	1.8	2.2	3.7	4.0	4.1	4.4
8H	4H	1.1	1.5	1.5	1.9	2.3	3.7	4.1	4.1	4.5
	6H	1.0	1.3	1.5	1.7	2.2	3.6	3.9	4.0	4.3
	8H	1.0	1.2	1.4	1.7	2.1	3.5	3.8	4.0	4.2
	12H	0.9	1.1	1.4	1.6	2.1	3.5	3.7	4.0	4.2
12H	4H	1.1	1.4	1.5	1.8	2.2	3.6	4.0	4.1	4.4
	6H	1.0	1.2	1.4	1.7	2.1	3.5	3.8	4.0	4.2
	8H	0.9	1.1	1.4	1.6	2.1	3.5	3.7	4.0	4.2
Variations with the observer position at spacings:										
S = 1.0H		+ 2.7 / -10.8				+ 3.9 / - 8.5				
1.5H		+ 4.1 / - 5.6				+ 5.8 / - 6.5				
2.0H		+ 4.8 / -10.6				+ 5.6 / -10.9				

CIE Pub.117, 549.0 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -2.1)

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-15

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:48.00V I:0.1100A P:5.280W PF:1.000 Freq:49.99Hz Lamp Flux:549.03x1 lm		
NAME: TLS-R35SXXBS35WA-T6NW9X-DC	TYPE:	WEIGHT:
SPEC.: TLS-R35SXXBS35WA-T6NW9X-DC	DIM.: 500*25*25mm	SERIAL No.:
MFR.: COLORS	SUR.:500*25mm	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	90	84	81	89	84	80	88	83	80	77
0.80	97	91	88	96	91	88	95	90	87	84
1.00	101	96	92	100	95	92	98	95	91	87
1.25	104	100	96	103	99	96	101	98	95	91
1.50	107	102	99	105	102	99	103	100	98	93
2.00	109	105	102	108	104	101	105	102	100	94
2.50	111	107	104	109	106	103	106	103	101	95
3.00	112	109	106	110	107	105	107	104	103	96
4.00	114	111	109	112	110	108	108	106	105	97
5.00	115	113	111	113	111	110	109	107	106	98
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-09-15

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:48.00V I:0.1100A P:5.280W PF:1.000 Freq:49.99Hz Lamp Flux:549.03x1 lm		
NAME: TLS-R35SXXBS35WA-T6NW9X-DC	TYPE:	WEIGHT:
SPEC.: TLS-R35SXXBS35WA-T6NW9X-DC	DIM.: 500*25*25mm	SERIAL No.:
MFR.: COLORS	SUR.:500*25mm	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-15

Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

AAI Figure

Test:U:48.00V I:0.1100A P:5.280W PF:1.000 Freq:49.99Hz Lamp Flux:549.03x1 lm		
NAME: TLS-R35SXXBS35WA-T6NW9X-DC	TYPE:	WEIGHT:
SPEC.: TLS-R35SXXBS35WA-T6NW9X-DC	DIM.: 500*25*25mm	SERIAL No.:
MFR.: COLORS	SUR.:500*25mm	Shielding Angle:

Flux out:306.5 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-15

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


Test:U:48.00V I:0.1100A P:5.280W PF:1.000 Freq:49.99Hz Lamp Flux:549.03x1 lm		
NAME: TLS-R35SXXBS35WA-T6NW9X-DC	TYPE:	WEIGHT:
SPEC.: TLS-R35SXXBS35WA-T6NW9X-DC	DIM.: 500*25*25mm	SERIAL No.:
MFR.: COLORS	SUR.:500*25mm	Shielding Angle:



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: JYH
 Test Date: 2020-09-15

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity: 65.0%
 Test Distance: 10.950m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2020-09-15

Range: 0 - 180DEG
Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:48.00V I:0.1100A P:5.280W PF:1.000 Freq:49.99Hz Lamp Flux:549.03x1 lm		
NAME: TLS-R35SXXBS35WA-T6NW9X-DC	TYPE:	WEIGHT:
SPEC.: TLS-R35SXXBS35WA-T6NW9X-DC	DIM.: 500*25*25mm	SERIAL No.:
MFR.: COLORS	SUR.:500*25mm	Shielding Angle:

Table--1

UNIT: cd

C(DEG) g (DEG)	0	45	90	135	180	225	270	315										
0	2619	2635	2628	2604	2619	2635	2628	2604										
5	2128	2286	2467	2608	2662	2540	2362	2148										
10	1275	1568	1910	2191	2242	1962	1616	1295										
15	476	713	1043	1393	1418	1038	700	478										
20	168	234	375	566	562	332	203	146										
25	75.6	97.1	131	178	144	98.5	72.6	54.9										
30	40.5	53.5	69.3	81.6	54.8	44.8	36.1	29.0										
35	19.5	27.4	37.4	44.9	29.1	24.1	19.9	15.6										
40	8.87	12.9	18.0	22.0	16.1	12.6	9.83	7.48										
45	4.42	5.86	7.99	9.97	8.16	5.68	4.53	3.82										
50	2.52	3.44	4.36	4.82	3.99	3.33	2.67	2.15										
55	1.08	1.70	2.51	2.79	2.32	1.77	1.28	0.89										
60	0.33	0.59	1.12	1.26	0.96	0.66	0.48	0.25										
65	0.17	0.24	0.31	0.39	0.21	0.20	0.10	0.13										
70	0.09	0.08	0.20	0.19	0.09	0.12	0.01	0.07										
75	0.04	0.00	0.09	0.05	0.01	0.06	0.00	0.03										
80	0.00	0.00	0.04	0.00	0.00	0.02	0.00	0.01										
85	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00										
90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00										
95	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00										
100	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00										
105	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00										
110	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00										
115	0.00	0.01	0.00	0.00	0.00	0.00	0.01	0.00										
120	0.00	0.03	0.00	0.01	0.01	0.00	0.03	0.00										
125	0.00	0.06	0.00	0.03	0.03	0.00	0.07	0.00										
130	0.11	0.13	0.01	0.08	0.07	0.02	0.11	0.09										
135	0.33	0.29	0.19	0.15	0.13	0.17	0.27	0.29										
140	0.71	0.60	0.39	0.34	0.31	0.35	0.55	0.63										
145	1.30	1.11	0.80	0.69	0.61	0.66	0.98	1.16										
150	2.51	2.04	1.47	1.23	1.07	1.20	1.66	2.18										
155	5.57	4.14	2.84	2.25	1.93	2.31	3.25	5.01										
160	14.0	10.2	6.22	4.74	4.16	5.18	7.50	12.2										
165	26.2	22.6	15.0	11.0	10.2	10.8	13.3	20.5										
170	30.3	32.1	25.3	19.0	17.0	14.2	14.4	19.4										
175	22.9	28.4	25.6	20.4	17.1	14.1	13.0	14.9										
180	19.5	20.2	19.4	17.9	19.5	20.2	19.4	17.9										

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-15

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks: