


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:48.00V I:0.2960A P:14.20W PF:1.000 Freq:49.99Hz Lamp Flux:953.854x1 lm		
NAME: TLS-RNR30NKXB1000-I14NW9X-BC	TYPE:	WEIGHT:
SPEC.: TLS-RNR30NKXB1000-I14NW9X-BC	DIM.: 1000*25*25mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*25mm	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 67.17 lm/W			
TLS-RNR30NKXB1000-I14NW9X-BC		Imax(cd)	147.7	S/MH(C0/180)	1.74
NOMINAL POWER(W)	14	LOR(%)	100.0	S/MH(C90/270)	1.25
RATED VOLTAGE(V)	48	TOTAL FLUX(lm)	953.85	h UP,DN(C0-180)	16.6,34.0
NOMINAL FLUX(lm)	953.854	CIE CLASS	SEMI-D.	h UP,DN(C180-360)	15.9,33.5
LAMPS INSIDE	1	h up(%)	32.5	CIBSE SHR NOM	1.50
TEST VOLTAGE(V)	48	h down(%)	67.5	CIBSE SHR MAX	1.55

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-15

Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	124.8	122.2	121.0	124.3	125.8	124.4	121.2	122.3	0- 10	11.76	11.76	1.23,1.23
20	131.2	121.2	114.2	124.5	131.0	124.6	114.4	121.4	10- 20	34.90	46.66	4.89,4.89
30	137.5	120.0	103.3	122.8	135.8	122.7	103.7	120.2	20- 30	56.41	103.1	10.8,10.8
40	142.1	117.1	88.97	118.8	138.8	118.3	89.40	117.8	30- 40	74.55	177.6	18.6,18.6
50	144.9	112.3	71.89	112.9	139.9	112.0	72.36	113.5	40- 50	87.70	265.3	27.8,27.8
60	146.8	106.3	52.82	106.2	139.9	104.6	53.15	108.2	50- 60	95.19	360.5	37.8,37.8
70	147.6	100.6	32.82	99.47	138.9	97.46	32.91	103.0	60- 70	97.40	457.9	48,48
80	147.2	95.82	14.10	93.33	136.6	91.07	13.91	98.81	70- 80	95.35	553.3	58,58
90	144.1	91.62	1.839	87.18	132.0	84.76	1.595	94.97	80- 90	90.41	643.7	67.5,67.5
100	137.0	86.07	0.9553	77.66	123.2	75.00	1.164	82.26	90-100	84.31	728.0	76.3,76.3
110	122.7	74.24	1.028	64.62	107.0	61.86	2.854	75.87	100-110	72.49	800.5	83.9,83.9
120	105.6	55.80	1.589	50.03	89.18	46.01	4.458	63.42	110-120	57.79	858.3	90,90
130	86.50	40.69	1.782	37.47	69.85	34.92	5.917	49.86	120-130	41.65	899.9	94.3,94.3
140	66.49	28.73	1.803	25.26	50.61	23.38	7.116	38.15	130-140	27.69	927.6	97.2,97.2
150	43.71	17.01	1.896	13.61	31.84	12.76	7.976	28.08	140-150	15.76	943.4	98.9,98.9
160	27.25	9.815	3.048	6.786	14.97	6.373	8.544	19.54	150-160	7.349	950.7	99.7,99.7
170	4.238	6.370	5.722	3.373	4.054	3.515	8.563	12.53	160-170	2.616	953.3	99.9,99.9
180	2.224	5.344	8.643	7.461	2.191	5.818	7.989	7.474	170-180	0.5350	953.9	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-09-15

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:48.00V I:0.2960A P:14.20W PF:1.000 Freq:49.99Hz Lamp Flux:953.854x1 lm		
NAME: TLS-RNR30NKXBX1000-I14NW9X-BC	TYPE:	WEIGHT:
SPEC.: TLS-RNR30NKXBX1000-I14NW9X-BC	DIM.: 1000*25*25mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*25mm	Shielding Angle:



LUMINANCE cd/(m2)		
G(DEG)	C0/180	C90/270
85	66977	3109
80	33915	3249
75	22826	3557
70	17268	3838
65	13947	4057
60	11742	4225
55	10181	4360
50	9020	4474
45	8125	4567


C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-09-15

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:48.00V I:0.2960A P:14.20W PF:1.000 Freq:49.99Hz Lamp Flux:953.854x1 lm		
NAME: TLS-RNR30NKXB1000-I14NW9X-BC	TYPE:	WEIGHT:
SPEC.: TLS-RNR30NKXB1000-I14NW9X-BC	DIM.: 1000*25*25mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*25mm	Shielding Angle:

r _{cc}	80%			70%			50%			30%			10%			0
r _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Coefficients of Utilization(CU)															
0.0	1.11	1.11	1.11	1.05	1.05	1.05	.93	.93	.93	.82	.82	.82	.72	.72	.72	.67
1.0	.91	.85	.80	.85	.80	.76	.75	.71	.67	.65	.62	.59	.57	.54	.52	.47
2.0	.77	.69	.62	.72	.65	.59	.63	.57	.52	.55	.50	.46	.47	.44	.41	.36
3.0	.66	.57	.50	.62	.54	.47	.54	.48	.42	.47	.42	.37	.41	.36	.33	.29
4.0	.58	.48	.41	.54	.46	.39	.48	.40	.35	.41	.36	.31	.36	.31	.27	.24
5.0	.51	.41	.34	.48	.39	.33	.42	.35	.29	.37	.31	.26	.32	.27	.23	.20
6.0	.46	.36	.29	.43	.34	.28	.38	.31	.25	.33	.27	.22	.28	.24	.20	.17
7.0	.41	.32	.25	.39	.30	.24	.34	.27	.22	.30	.24	.20	.26	.21	.17	.15
8.0	.37	.28	.22	.35	.27	.21	.31	.24	.19	.27	.21	.17	.24	.19	.15	.13
9.0	.34	.25	.20	.32	.24	.19	.28	.22	.17	.25	.19	.15	.22	.17	.14	.11
10.0	.31	.23	.18	.29	.22	.17	.26	.20	.15	.23	.18	.14	.20	.16	.12	.10



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-15

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:48.00V I:0.2960A P:14.20W PF:1.000 Freq:49.99Hz Lamp Flux:953.854x1 lm		
NAME: TLS-RNR30NKXBX1000-II14NW9X-BC	TYPE:	WEIGHT:
SPEC.:TLS-RNR30NKXBX1000-II14NW9X-BC	DIM.: 1000*25*25mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*25mm	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Wall Exitance Coefficients(WEC)															
0.0																
1.0	.411	.234	.074	.394	.225	.071	.362	.208	.066	.333	.192	.062	.305	.177	.057	
2.0	.347	.190	.058	.331	.182	.056	.302	.168	.052	.275	.154	.048	.250	.141	.045	
3.0	.303	.161	.048	.289	.155	.047	.263	.142	.043	.238	.130	.040	.215	.119	.037	
4.0	.271	.141	.041	.258	.135	.040	.233	.124	.037	.211	.113	.034	.190	.103	.031	
5.0	.245	.125	.036	.233	.120	.035	.211	.110	.032	.190	.100	.030	.170	.091	.027	
6.0	.223	.112	.032	.212	.107	.031	.192	.098	.029	.173	.090	.026	.155	.082	.024	
7.0	.205	.101	.029	.195	.097	.028	.176	.089	.026	.159	.081	.024	.142	.074	.022	
8.0	.190	.093	.026	.181	.089	.025	.163	.081	.023	.147	.074	.021	.131	.067	.020	
9.0	.176	.085	.024	.168	.082	.023	.152	.075	.021	.137	.068	.020	.122	.062	.018	
10.0	.165	.079	.022	.157	.076	.021	.142	.069	.020	.128	.063	.018	.114	.057	.016	

rcc	80%			70%			50%			30%			10%			0	
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
rfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)										
0.0	.438	.438	.438	.375	.375	.375	.256	.256	.256	.147	.147	.147	.047	.047	.047		
1.0	.437	.405	.376	.374	.348	.324	.256	.239	.224	.147	.138	.130	.047	.045	.042		
2.0	.431	.383	.343	.369	.330	.296	.253	.228	.207	.146	.133	.121	.047	.043	.039		
3.0	.424	.367	.322	.363	.317	.280	.249	.220	.196	.144	.129	.116	.046	.042	.038		
4.0	.416	.355	.309	.357	.307	.268	.246	.214	.189	.142	.125	.112	.046	.041	.037		
5.0	.408	.346	.300	.351	.299	.261	.242	.209	.184	.140	.123	.109	.045	.040	.036		
6.0	.401	.338	.293	.345	.293	.255	.238	.205	.181	.138	.121	.107	.045	.039	.035		
7.0	.394	.332	.289	.339	.288	.251	.234	.202	.178	.136	.119	.106	.044	.039	.035		
8.0	.387	.327	.285	.333	.283	.248	.231	.199	.176	.134	.117	.105	.043	.038	.035		
9.0	.381	.322	.282	.328	.279	.246	.227	.196	.175	.132	.116	.104	.043	.038	.035		
10.0	.375	.318	.280	.323	.276	.244	.224	.194	.173	.131	.115	.104	.042	.038	.034		

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-15

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:48.00V I:0.2960A P:14.20W PF:1.000 Freq:49.99Hz Lamp Flux:953.854x1 lm											
NAME: TLS-RNR30NKXBX1000-I14NW9X-BC						TYPE:		WEIGHT:			
SPEC.:TLS-RNR30NKXBX1000-I14NW9X-BC						DIM.: 1000*25*25mm		SERIAL No.:			
MFR.: COLORS						SUR.:1000*25mm		Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	19.6	20.9	20.3	21.6	22.4	16.1	17.3	16.8	18.0	18.9	
	23.0	24.1	23.7	24.8	25.7	17.7	18.9	18.5	19.6	20.5	
	24.9	26.0	25.6	26.7	27.6	18.5	19.5	19.2	20.3	21.2	
	27.0	28.0	27.8	28.8	29.7	19.0	20.0	19.7	20.8	21.7	
	28.2	29.2	29.0	30.0	30.9	19.2	20.2	20.0	21.0	21.9	
	29.6	30.5	30.3	31.3	32.3	19.3	20.3	20.1	21.1	22.0	
4H	20.2	21.2	20.9	22.0	22.9	17.8	18.9	18.5	19.6	20.5	
	23.7	24.7	24.5	25.4	26.4	19.8	20.8	20.6	21.6	22.5	
	25.8	26.7	26.6	27.5	28.4	20.8	21.7	21.6	22.5	23.5	
	28.1	28.9	29.0	29.8	30.8	21.6	22.4	22.4	23.2	24.3	
	29.5	30.2	30.3	31.0	32.1	22.0	22.7	22.8	23.5	24.6	
	31.0	31.7	31.8	32.5	33.5	22.2	22.9	23.1	23.7	24.8	
8H	26.1	26.9	27.0	27.7	28.7	22.5	23.2	23.3	24.1	25.1	
	28.8	29.4	29.6	30.3	31.3	23.8	24.5	24.7	25.3	26.4	
	30.3	30.9	31.2	31.7	32.8	24.5	25.0	25.3	25.9	27.0	
	32.1	32.6	32.9	33.5	34.5	25.0	25.5	25.9	26.4	27.5	
12H	26.2	26.8	27.0	27.7	28.7	23.1	23.7	23.9	24.6	25.6	
	28.9	29.5	29.8	30.3	31.4	24.7	25.3	25.6	26.2	27.2	
	30.5	31.0	31.4	31.9	33.0	25.6	26.1	26.5	27.0	28.1	
Variations with the observer position at spacings:											
S = 1.0H	+ 0.1 / - 0.1					+ 0.1 / - 0.1					
1.5H	+ 0.2 / - 0.2					+ 0.2 / - 0.3					
2.0H	+ 0.3 / - 0.3					+ 0.3 / - 0.4					

CIE Pub.117, 953.9 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -0.2)

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-15

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:48.00V I:0.2960A P:14.20W PF:1.000 Freq:49.99Hz Lamp Flux:953.854x1 lm		
NAME: TLS-RNR30NKXB1000-II14NW9X-BC	TYPE:	WEIGHT:
SPEC.: TLS-RNR30NKXB1000-II14NW9X-BC	DIM.: 1000*25*25mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*25mm	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	41	29	21	40	28	21	37	27	20	13
0.80	50	36	28	48	35	27	44	33	26	18
1.00	58	44	35	55	42	34	50	42	32	22
1.25	64	51	41	61	49	40	56	45	38	26
1.50	70	56	47	66	54	45	60	50	42	30
2.00	77	65	56	73	62	54	66	57	49	35
2.50	82	71	62	78	67	59	69	61	54	38
3.00	86	75	67	81	72	64	72	65	59	42
4.00	91	82	74	86	78	71	76	70	64	46
5.00	94	86	80	89	82	76	79	73	68	49
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-15

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:48.00V I:0.2960A P:14.20W PF:1.000 Freq:49.99Hz Lamp Flux:953.854x1 lm		
NAME: TLS-RNR30NKXB1000-I14NW9X-BC	TYPE:	WEIGHT:
SPEC.: TLS-RNR30NKXB1000-I14NW9X-BC	DIM.: 1000*25*25mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*25mm	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-15

deg Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

AAI Figure

Test:U:48.00V I:0.2960A P:14.20W PF:1.000 Freq:49.99Hz Lamp Flux:953.854x1 lm		
NAME: TLS-RNR30NKXB1000-I14NW9X-BC	TYPE:	WEIGHT:
SPEC.: TLS-RNR30NKXB1000-I14NW9X-BC	DIM.: 1000*25*25mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*25mm	Shielding Angle:

Flux out:321.9 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-15

g Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


Test:U:48.00V I:0.2960A P:14.20W PF:1.000 Freq:49.99Hz Lamp Flux:953.854x1 lm		
NAME: TLS-RNR30NKXB1000-I14NW9X-BC	TYPE:	WEIGHT:
SPEC.: TLS-RNR30NKXB1000-I14NW9X-BC	DIM.: 1000*25*25mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*25mm	Shielding Angle:



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: JYH
 Test Date: 2020-09-15

Range: 0 - 180DEG
 Interval: 1.0DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity: 65.0%
 Test Distance: 10.950m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: JYH
 Test Date: 2020-09-15

Range: 0 - 180DEG
 Interval: 1.0DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity: 65.0%
 Test Distance: 10.950m [K=1.0000]
 Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:48.00V I:0.2960A P:14.20W PF:1.000 Freq:49.99Hz Lamp Flux:953.854x1 lm		
NAME: TLS-RNR30NKXB1000-I14NW9X-BC	TYPE:	WEIGHT:
SPEC.: TLS-RNR30NKXB1000-I14NW9X-BC	DIM.: 1000*25*25mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*25mm	Shielding Angle:

Table--1

UNIT: cd

C(DEG) g (DEG)	0	45	90	135	180	225	270	315										
0	122	123	123	123	122	123	123	123										
5	123	123	123	124	124	124	123	123										
10	125	122	121	124	126	124	121	122										
15	128	122	118	125	128	125	118	122										
20	131	121	114	125	131	125	114	121										
25	135	121	109	124	134	124	110	121										
30	138	120	103	123	136	123	104	120										
35	140	119	96.5	121	138	121	96.9	119										
40	142	117	89.0	119	139	118	89.4	118										
45	144	115	80.7	116	140	115	81.2	116										
50	145	112	71.9	113	140	112	72.4	114										
55	146	109	62.5	110	140	108	62.9	111										
60	147	106	52.8	106	140	105	53.2	108										
65	147	103	42.9	103	140	101	43.0	106										
70	148	101	32.8	99.5	139	97.5	32.9	103										
75	148	98.1	23.0	96.3	138	94.2	23.1	101										
80	147	95.8	14.1	93.3	137	91.1	13.9	98.8										
85	146	93.7	6.77	90.2	135	87.9	6.51	96.8										
90	144	91.6	1.84	87.2	132	84.8	1.59	95.0										
95	142	90.0	1.01	84.3	130	81.8	0.94	90.7										
100	137	86.1	0.96	77.7	123	75.0	1.16	82.3										
105	130	81.5	0.96	71.3	115	68.3	2.01	80.4										
110	123	74.2	1.03	64.6	107	61.9	2.85	75.9										
115	114	66.9	1.33	57.4	98.4	53.5	3.69	69.8										
120	106	55.8	1.59	50.0	89.2	46.0	4.46	63.4										
125	96.3	47.0	1.71	43.4	79.6	40.7	5.20	56.5										
130	86.5	40.7	1.78	37.5	69.9	34.9	5.92	49.9										
135	76.6	35.2	1.80	31.3	60.2	29.1	6.56	44.1										
140	66.5	28.7	1.80	25.3	50.6	23.4	7.12	38.2										
145	56.2	22.5	1.82	19.2	41.1	17.9	7.59	32.8										
150	43.7	17.0	1.90	13.6	31.8	12.8	7.98	28.1										
155	35.5	12.8	2.17	9.77	23.1	8.91	8.29	23.8										
160	27.3	9.81	3.05	6.79	15.0	6.37	8.54	19.5										
165	18.9	7.51	4.28	4.63	7.70	4.62	8.61	15.6										
170	4.24	6.37	5.72	3.37	4.05	3.52	8.56	12.5										
175	2.55	5.74	7.25	3.58	2.43	3.01	8.37	9.86										
180	2.22	5.34	8.64	7.46	2.19	5.82	7.99	7.47										

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-15

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks: