


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:24.00V I:0.2020A P:4.840W PF:1.000 Freq:0Hz Lamp Flux:982.463x1 lm		
NAME: D8902410NO	TYPE:	WEIGHT:
SPEC.:D8902410NO-8WWNSA012WC0100	DIM.: 1000*10*1.5mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*10	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 202.99 lm/W			
MODEL	D8902410NO	I _{max} (cd)	323.1	S/MH(C0/180)	1.28
NOMINAL POWER(W)	4.8	LOR(%)	100.0	S/MH(C90/270)	1.27
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	982.46	h UP,DN(C0-180)	0.9,49.6
NOMINAL FLUX(lm)	982.463	CIE CLASS	DIRECT	h UP,DN(C180-360)	0.8,48.7
LAMPS INSIDE	1	h up(%)	1.7	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	24	h down(%)	98.3	CIBSE SHR MAX	1.35



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-29

Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	316.2	317.9	318.9	319.7	317.9	317.1	316.4	316.3	0- 10	30.55	30.55	3.11,3.11
20	300.7	303.7	305.5	306.7	304.2	302.2	300.6	300.2	10- 20	87.96	118.5	12.1,12.1
30	276.0	280.0	282.5	284.1	280.9	277.8	275.5	274.8	20- 30	134.7	253.2	25.8,25.8
40	242.1	247.0	249.9	251.8	248.4	244.4	241.6	240.5	30- 40	164.8	418.0	42.5,42.5
50	199.6	204.9	208.1	210.2	206.9	202.2	199.1	197.6	40- 50	174.1	592.1	60.3,60.3
60	149.0	154.4	157.7	160.0	157.0	152.2	148.9	147.1	50- 60	160.2	752.3	76.6,76.6
70	91.98	97.06	100.00	102.2	100.1	95.47	92.45	90.50	60- 70	123.9	876.1	89.2,89.2
80	35.18	39.13	40.35	42.99	41.98	38.60	36.31	34.61	70- 80	70.58	946.7	96.4,96.4
90	3.576	4.122	2.473	5.042	3.913	3.635	1.362	2.698	80- 90	19.19	965.9	98.3,98.3
100	1.296	1.303	1.089	1.229	0.8230	0.8138	0.8517	0.9200	90-100	1.466	967.4	98.5,98.5
110	1.923	1.898	1.681	1.731	1.684	1.508	1.920	1.616	100-110	1.450	968.8	98.6,98.6
120	2.778	2.807	2.783	2.540	2.480	2.182	2.732	2.558	110-120	2.170	971.0	98.8,98.8
130	3.499	3.587	3.605	3.226	3.180	2.764	3.107	3.313	120-130	2.656	973.6	99.1,99.1
140	4.027	4.195	4.167	3.707	3.741	3.290	3.286	3.720	130-140	2.737	976.4	99.4,99.4
150	4.382	4.543	4.408	4.135	4.082	3.753	3.373	3.720	140-150	2.455	978.8	99.6,99.6
160	4.742	4.595	4.576	4.502	4.443	4.155	3.621	3.727	150-160	1.929	980.8	99.8,99.8
170	4.843	4.589	4.789	4.670	4.555	4.388	4.483	3.913	160-170	1.245	982.0	100,100
180	4.796	5.130	5.444	5.230	4.789	5.110	5.444	5.230	170-180	0.4487	982.5	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-01-29

g Range: 0 - 180DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:24.00V I:0.2020A P:4.840W PF:1.000 Freq:0Hz Lamp Flux:982.463x1 lm		
NAME: D8902410NO	TYPE:	WEIGHT:
SPEC.:D8902410NO-8WWNSA012WC0100	DIM.: 1000*10*1.5mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*10	Shielding Angle:



LUMINANCE cd/(m2)		
G(180)	C0/180	C90/270
85	15725	18431
80	20258	23239
75	24187	26980
70	26893	29237
65	28659	30652
60	29802	31543
55	30552	32076
50	31046	32380
45	31385	32550


C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-01-29

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:24.00V I:0.2020A P:4.840W PF:1.000 Freq:0Hz Lamp Flux:982.463x1 lm		
NAME: D8902410NO	TYPE:	WEIGHT:
SPEC.:D8902410NO-8WWNSA012WC0100	DIM.: 1000*10*1.5mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*10	Shielding Angle:

r _{cc}	80%			70%			50%			30%			10%			0
r _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Coefficients of Utilization(CU)															
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.10	1.10	1.10	1.05	1.05	1.05	1.00	1.00	1.00	.98
1.0	1.03	.99	.95	1.01	.97	.93	.96	.93	.90	.92	.89	.87	.88	.86	.84	.82
2.0	.90	.83	.77	.88	.81	.76	.84	.78	.74	.80	.76	.72	.77	.73	.70	.68
3.0	.79	.70	.64	.77	.69	.63	.74	.67	.62	.71	.65	.60	.68	.63	.59	.57
4.0	.69	.60	.54	.68	.60	.53	.65	.58	.52	.63	.56	.51	.60	.55	.50	.48
5.0	.62	.53	.46	.61	.52	.46	.58	.51	.45	.56	.50	.44	.54	.48	.44	.42
6.0	.56	.47	.40	.55	.46	.40	.53	.45	.39	.51	.44	.39	.49	.43	.38	.36
7.0	.50	.41	.35	.49	.41	.35	.48	.40	.35	.46	.39	.34	.45	.39	.34	.32
8.0	.46	.37	.31	.45	.37	.31	.44	.36	.31	.42	.36	.31	.41	.35	.30	.28
9.0	.42	.34	.28	.41	.33	.28	.40	.33	.28	.39	.32	.28	.38	.32	.27	.25
10.0	.39	.31	.25	.38	.31	.25	.37	.30	.25	.36	.30	.25	.35	.29	.25	.23



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-29

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:24.00V I:0.2020A P:4.840W PF:1.000 Freq:0Hz Lamp Flux:982.463x1 lm		
NAME: D8902410NO	TYPE:	WEIGHT:
SPEC.:D8902410NO-8WWNSA012WC0100	DIM.: 1000*10*1.5mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*10	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Wall Exitance Coefficients(WEC)															
0.0																
1.0	.314	.178	.057	.306	.175	.055	.292	.167	.053	.279	.161	.052	.267	.155	.050	
2.0	.295	.162	.050	.288	.159	.049	.276	.153	.048	.264	.148	.046	.253	.143	.045	
3.0	.273	.145	.043	.267	.143	.043	.255	.138	.042	.245	.134	.041	.235	.130	.040	
4.0	.251	.131	.038	.246	.129	.038	.236	.125	.037	.227	.122	.037	.218	.119	.036	
5.0	.232	.118	.034	.227	.117	.034	.219	.114	.033	.210	.111	.033	.202	.108	.033	
6.0	.215	.108	.031	.211	.107	.031	.203	.104	.030	.196	.102	.030	.189	.099	.029	
7.0	.200	.099	.028	.196	.098	.028	.189	.096	.028	.182	.094	.027	.176	.092	.027	
8.0	.187	.091	.026	.183	.090	.026	.177	.088	.025	.171	.087	.025	.165	.085	.025	
9.0	.175	.085	.024	.172	.084	.024	.166	.082	.023	.161	.081	.023	.155	.079	.023	
10.0	.164	.079	.022	.162	.078	.022	.156	.077	.022	.151	.075	.021	.147	.074	.021	

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Ceiling Cavity Exitance Coefficients(CCEC)															
0.0	.203	.203	.203	.174	.174	.174	.119	.119	.119	.068	.068	.068	.022	.022	.022	
1.0	.194	.169	.147	.166	.145	.127	.113	.100	.087	.065	.058	.051	.021	.019	.016	
2.0	.186	.145	.111	.159	.125	.096	.109	.086	.067	.063	.050	.039	.020	.016	.013	
3.0	.178	.127	.087	.153	.110	.075	.105	.076	.053	.061	.045	.031	.019	.014	.010	
4.0	.171	.114	.071	.146	.099	.062	.101	.069	.044	.058	.040	.026	.019	.013	.008	
5.0	.163	.104	.060	.140	.090	.052	.097	.063	.037	.056	.037	.022	.018	.012	.007	
6.0	.156	.096	.052	.134	.083	.045	.092	.058	.032	.054	.034	.019	.017	.011	.006	
7.0	.149	.089	.046	.128	.077	.040	.089	.054	.029	.052	.032	.017	.017	.010	.006	
8.0	.143	.083	.042	.123	.072	.037	.085	.050	.026	.049	.030	.015	.016	.010	.005	
9.0	.137	.078	.038	.118	.068	.034	.082	.048	.024	.047	.028	.014	.015	.009	.005	
10.0	.131	.074	.036	.113	.064	.031	.078	.045	.022	.046	.027	.013	.015	.009	.004	

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-29

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:24.00V I:0.2020A P:4.840W PF:1.000 Freq:0Hz Lamp Flux:982.463x1 lm											
NAME: D8902410NO						TYPE:		WEIGHT:			
SPEC.:D8902410NO-8WWNSA012WC0100						DIM.: 1000*10*1.5mm		SERIAL No.:01			
MFR.: COLORS						SUR.:1000*10		Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	24.8	26.3	25.1	26.6	26.8	25.0	26.5	25.3	26.8	27.0	
	3H	26.3	27.7	26.6	28.0	28.3	26.6	28.0	26.9	28.3	28.5
	4H	26.9	28.2	27.2	28.5	28.8	27.2	28.5	27.6	28.8	29.1
	6H	27.2	28.5	27.6	28.8	29.1	27.6	28.9	28.0	29.2	29.5
	8H	27.3	28.5	27.7	28.9	29.2	27.8	29.0	28.1	29.3	29.6
	12H	27.4	28.5	27.7	28.9	29.2	27.8	29.0	28.2	29.3	29.6
4H	2H	25.5	26.8	25.8	27.1	27.4	25.6	26.9	26.0	27.2	27.5
	3H	27.1	28.3	27.5	28.6	29.0	27.4	28.5	27.8	28.9	29.2
	4H	27.8	28.9	28.2	29.2	29.6	28.1	29.2	28.5	29.5	29.9
	6H	28.3	29.2	28.7	29.6	30.0	28.7	29.6	29.1	30.0	30.4
	8H	28.4	29.3	28.9	29.7	30.1	28.8	29.7	29.3	30.1	30.5
	12H	28.5	29.3	29.0	29.7	30.2	28.9	29.7	29.4	30.1	30.6
8H	4H	28.1	29.0	28.5	29.4	29.8	28.4	29.2	28.8	29.6	30.1
	6H	28.7	29.4	29.2	29.9	30.3	29.0	29.8	29.5	30.2	30.7
	8H	28.9	29.6	29.4	30.0	30.5	29.3	29.9	29.8	30.4	30.9
	12H	29.1	29.6	29.6	30.1	30.6	29.4	30.0	29.9	30.5	31.0
12H	4H	28.1	28.9	28.6	29.3	29.8	28.4	29.2	28.8	29.6	30.0
	6H	28.8	29.4	29.3	29.9	30.4	29.1	29.7	29.6	30.2	30.7
	8H	29.0	29.6	29.5	30.1	30.6	29.4	29.9	29.9	30.4	30.9
Variations with the observer position at spacings:											
S = 1.0H	+ 0.2 / - 0.2					+ 0.1 / - 0.2					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					
2.0H	+ 0.2 / - 0.4					+ 0.2 / - 0.3					

CIE Pub.117, 982.5 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -0.1)

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-29

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:24.00V I:0.2020A P:4.840W PF:1.000 Freq:0Hz Lamp Flux:982.463x1 lm		
NAME: D8902410NO	TYPE:	WEIGHT:
SPEC.:D8902410NO-8WWNSA012WC0100	DIM.: 1000*10*1.5mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*10	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	56	45	37	55	44	37	54	44	37	31
0.80	66	55	47	65	54	47	63	53	46	39
1.00	75	63	56	73	63	56	71	64	55	48
1.25	82	71	64	80	70	63	77	69	63	55
1.50	87	77	70	85	76	69	82	74	68	60
2.00	94	85	79	92	84	78	88	81	76	68
2.50	98	90	84	96	89	83	92	86	81	72
3.00	101	94	89	99	93	88	95	90	85	76
4.00	106	100	95	103	98	93	98	94	91	81
5.00	108	103	99	105	101	97	101	97	94	84
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-01-29

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:24.00V I:0.2020A P:4.840W PF:1.000 Freq:0Hz Lamp Flux:982.463x1 lm		
NAME: D8902410NO	TYPE:	WEIGHT:
SPEC.:D8902410NO-8WWNSA012WC0100	DIM.: 1000*10*1.5mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*10	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-29

deg Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

AAI Figure

Test:U:24.00V I:0.2020A P:4.840W PF:1.000 Freq:0Hz Lamp Flux:982.463x1 lm		
NAME: D8902410NO	TYPE:	WEIGHT:
SPEC.:D8902410NO-8WWNSA012WC0100	DIM.: 1000*10*1.5mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*10	Shielding Angle:

Flux out:737.5 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-29

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


Test:U:24.00V I:0.2020A P:4.840W PF:1.000 Freq:0Hz Lamp Flux:982.463x1 lm		
NAME: D8902410NO	TYPE:	WEIGHT:
SPEC.:D8902410NO-8WWNSA012WC0100	DIM.: 1000*10*1.5mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*10	Shielding Angle:



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-01-29

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: JYH
 Test Date: 2021-01-29

Range: 0 - 180DEG
 Interval: 1.0DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity: 65.0%
 Test Distance: 10.950m [K=1.0000]
 Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:24.00V I:0.2020A P:4.840W PF:1.000 Freq:0Hz Lamp Flux:982.463x1 lm		
NAME: D8902410NO	TYPE:	WEIGHT:
SPEC.:D8902410NO-8WWNSA012WC0100	DIM.: 1000*10*1.5mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*10	Shielding Angle:

Table--1

UNIT: cd

C(DEC) g (DEC)	0	45	90	135	180	225	270	315										
0	322	322	322	323	322	322	322	323										
5	320	321	322	323	321	321	321	321										
10	316	318	319	320	318	317	316	316										
15	310	312	313	314	312	311	310	309										
20	301	304	306	307	304	302	301	300										
25	290	293	295	297	294	291	289	289										
30	276	280	282	284	281	278	276	275										
35	260	265	267	269	266	262	260	259										
40	242	247	250	252	248	244	242	240										
45	222	227	230	232	229	224	221	220										
50	200	205	208	210	207	202	199	198										
55	175	181	184	186	183	178	175	173										
60	149	154	158	160	157	152	149	147										
65	121	126	130	132	129	124	121	119										
70	92.0	97.1	100.0	102	100	95.5	92.5	90.5										
75	62.6	67.3	69.8	72.1	70.5	66.3	63.5	61.6										
80	35.2	39.1	40.4	43.0	42.0	38.6	36.3	34.6										
85	13.7	16.3	16.1	18.9	18.3	16.1	14.3	13.4										
90	3.58	4.12	2.47	5.04	3.91	3.63	1.36	2.70										
95	1.36	1.35	1.19	1.43	0.61	0.77	0.46	0.86										
100	1.30	1.30	1.09	1.23	0.82	0.81	0.85	0.92										
105	1.52	1.53	1.23	1.44	1.26	1.18	1.40	1.34										
110	1.92	1.90	1.68	1.73	1.68	1.51	1.92	1.62										
115	2.38	2.39	2.30	2.13	2.07	1.87	2.40	2.08										
120	2.78	2.81	2.78	2.54	2.48	2.18	2.73	2.56										
125	3.17	3.23	3.29	2.91	2.85	2.48	2.95	2.97										
130	3.50	3.59	3.60	3.23	3.18	2.76	3.11	3.31										
135	3.82	3.95	3.91	3.47	3.47	3.00	3.21	3.60										
140	4.03	4.19	4.17	3.71	3.74	3.29	3.29	3.72										
145	4.23	4.41	4.27	3.92	3.95	3.51	3.33	3.72										
150	4.38	4.54	4.41	4.13	4.08	3.75	3.37	3.72										
155	4.57	4.60	4.48	4.34	4.26	3.97	3.42	3.73										
160	4.74	4.60	4.58	4.50	4.44	4.15	3.62	3.73										
165	4.92	4.58	4.60	4.58	4.58	4.25	4.00	3.71										
170	4.84	4.59	4.79	4.67	4.55	4.39	4.48	3.91										
175	4.68	4.80	5.12	4.90	4.52	4.68	4.99	4.52										
180	4.80	5.13	5.44	5.23	4.79	5.11	5.44	5.23										

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-29

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks: