


## LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:24.00V I:0.1740A P:4.176W PF:1.000 Freq:0Hz Lamp Flux:897.69lx1 lm		
NAME: D8902410NO	TYPE:	WEIGHT:
SPEC.:D8902410NO-8NWNSA012WC0100	DIM.: 1000*10*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*10mm	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 214.96 lm/W			
MODEL	D8902410NO	I <sub>max</sub> (cd)	289.2	S/MH(C0/180)	1.28
NOMINAL POWER(W)	4.3	LOR(%)	100.0	S/MH(C90/270)	1.28
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	897.69	h UP,DN(C0-180)	0.9,49.4
NOMINAL FLUX(lm)	897.691	CIE CLASS	DIRECT	h UP,DN(C180-360)	0.8,48.8
LAMPS INSIDE	1	h up(%)	1.7	CIBSE SHR NOM	1.50
TEST VOLTAGE(V)	24	h down(%)	98.3	CIBSE SHR MAX	1.50



C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2021-01-21

Range: 0 - 180DEG  
Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

## ZONAL FLUX DIAGRAM

### ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	283.0	284.4	285.4	286.7	285.1	284.9	283.8	283.1	0- 10	27.36	27.36	3.05,3.05
20	269.6	271.8	273.9	276.1	273.9	272.5	270.4	268.7	10- 20	78.90	106.3	11.8,11.8
30	248.1	251.1	254.3	257.2	254.5	252.0	248.9	246.3	20- 30	121.2	227.5	25.3,25.3
40	218.7	222.2	226.3	229.9	227.0	223.5	219.5	216.2	30- 40	149.1	376.6	41.9,41.9
50	181.2	185.1	189.8	194.1	191.1	186.8	182.6	178.4	40- 50	158.5	535.1	59.6,59.6
60	136.0	139.9	145.1	149.9	147.0	142.6	138.1	133.4	50- 60	147.1	682.2	76,76
70	84.29	88.10	93.06	98.18	95.63	91.71	87.32	82.34	60- 70	115.1	797.3	88.8,88.8
80	32.10	35.02	38.75	43.49	41.54	38.69	35.21	31.14	70- 80	66.63	863.9	96.2,96.2
90	2.058	2.621	2.668	4.767	3.621	3.034	1.367	1.814	80- 90	18.25	882.1	98.3,98.3
100	1.249	1.290	1.196	1.283	0.8288	0.8069	0.8084	0.8611	90-100	1.291	883.4	98.4,98.4
110	1.881	1.832	1.514	1.772	1.705	1.569	1.630	1.735	100-110	1.425	884.9	98.6,98.6
120	2.712	2.646	2.331	2.519	2.534	2.290	2.185	2.544	110-120	2.077	886.9	98.8,98.8
130	3.393	3.241	2.966	3.128	3.201	2.824	2.619	2.991	120-130	2.481	889.4	99.1,99.1
140	3.913	3.641	3.386	3.554	3.714	3.286	2.933	3.173	130-140	2.521	891.9	99.4,99.4
150	4.148	3.861	3.720	3.922	4.035	3.767	3.313	3.306	140-150	2.263	894.2	99.6,99.6
160	4.474	4.041	4.127	4.328	4.335	4.195	4.081	3.540	150-160	1.818	896.0	99.8,99.8
170	4.589	4.529	4.761	4.716	4.354	4.582	4.756	4.388	160-170	1.230	897.2	99.9,99.9
180	4.475	5.123	5.210	5.310	4.475	5.130	5.250	5.324	170-180	0.4504	897.7	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG  
 C Interval: 45.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:JYH  
 Test Date:2021-01-21

g Range: 0 - 180DEG  
 Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
 Humidity:65.0%  
 Test Distance:10.950m [K=1.0000]  
 Remarks:

### LUMINANCE LIMITATION CURVES

Test:U:24.00V I:0.1740A P:4.176W PF:1.000 Freq:0Hz Lamp Flux:897.69lx1 lm		
NAME: D8902410NO	TYPE:	WEIGHT:
SPEC.:D8902410NO-8NWNSA012WC0100	DIM.: 1000*10*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*10mm	Shielding Angle:



LUMINANCE cd/(m2)		
G(180)	C0/180	C90/270
85	13457	18701
80	18484	22316
75	22206	25309
70	24644	27209
65	26194	28352
60	27195	29013
55	27804	29364
50	28195	29534
45	28416	29581


C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2021-01-21

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:24.00V I:0.1740A P:4.176W PF:1.000 Freq:0Hz Lamp Flux:897.69lx1 lm		
NAME: D8902410NO	TYPE:	WEIGHT:
SPEC.:D8902410NO-8NWN5A012WC0100	DIM.: 1000*10*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*10mm	Shielding Angle:

r <sub>cc</sub>	80%			70%			50%			30%			10%			0
r <sub>w</sub>	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r <sub>fc</sub>	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio                      Coefficients of Utilization(CU)															
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.10	1.10	1.10	1.05	1.05	1.05	1.00	1.00	1.00	.98
1.0	1.03	.99	.95	1.01	.97	.93	.96	.93	.90	.92	.89	.87	.88	.86	.84	.82
2.0	.89	.82	.77	.87	.81	.76	.84	.78	.73	.80	.75	.72	.77	.73	.70	.67
3.0	.78	.70	.63	.77	.69	.63	.73	.67	.61	.70	.65	.60	.67	.63	.59	.56
4.0	.69	.60	.53	.68	.59	.53	.65	.58	.52	.62	.56	.51	.60	.55	.50	.48
5.0	.62	.52	.46	.60	.52	.45	.58	.50	.45	.56	.49	.44	.54	.48	.43	.41
6.0	.55	.46	.40	.54	.46	.39	.52	.45	.39	.50	.44	.38	.49	.43	.38	.36
7.0	.50	.41	.35	.49	.41	.35	.47	.40	.34	.46	.39	.34	.44	.38	.34	.32
8.0	.46	.37	.31	.45	.37	.31	.43	.36	.31	.42	.35	.30	.41	.35	.30	.28
9.0	.42	.33	.28	.41	.33	.28	.40	.33	.27	.39	.32	.27	.37	.31	.27	.25
10.0	.38	.30	.25	.38	.30	.25	.37	.30	.25	.36	.29	.25	.35	.29	.24	.23



C Range: 0 - 360DEG  
 C Interval: 45.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:JYH  
 Test Date:2021-01-21

g Range: 0 - 180DEG  
 g Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
 Humidity:65.0%  
 Test Distance:10.950m [K=1.0000]  
 Remarks:

WEC AND CCEC

Test:U:24.00V I:0.1740A P:4.176W PF:1.000 Freq:0Hz Lamp Flux:897.69lx1 lm		
NAME: D8902410NO	TYPE:	WEIGHT:
SPEC.:D8902410NO-8NWN5A012WC0100	DIM.: 1000*10*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*10mm	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio                      Wall Exitance Coefficients(WEC)															
0.0																
1.0	.317	.180	.057	.309	.176	.056	.295	.169	.054	.282	.162	.052	.269	.156	.050	
2.0	.297	.163	.050	.290	.160	.049	.278	.154	.048	.266	.149	.047	.255	.144	.046	
3.0	.274	.146	.044	.268	.144	.043	.257	.139	.042	.247	.135	.041	.237	.131	.041	
4.0	.253	.131	.039	.247	.129	.038	.237	.126	.038	.228	.122	.037	.219	.119	.036	
5.0	.233	.119	.034	.229	.117	.034	.220	.114	.034	.211	.111	.033	.204	.109	.033	
6.0	.216	.108	.031	.212	.107	.031	.204	.104	.030	.196	.102	.030	.189	.100	.030	
7.0	.201	.099	.028	.197	.098	.028	.190	.096	.028	.183	.094	.027	.177	.092	.027	
8.0	.187	.092	.026	.184	.091	.026	.178	.089	.025	.172	.087	.025	.166	.085	.025	
9.0	.175	.085	.024	.172	.084	.024	.167	.082	.023	.161	.081	.023	.156	.079	.023	
10.0	.165	.079	.022	.162	.078	.022	.157	.077	.022	.152	.075	.021	.147	.074	.021	

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Ceiling Cavity Exitance Coefficients(CCEC)												
0.0	.204	.204	.204	.174	.174	.174	.119	.119	.119	.068	.068	.068	.022	.022	.022	
1.0	.194	.169	.147	.166	.145	.127	.114	.100	.088	.065	.058	.051	.021	.019	.016	
2.0	.186	.145	.111	.160	.125	.096	.109	.087	.067	.063	.050	.039	.020	.016	.013	
3.0	.179	.128	.087	.153	.110	.076	.105	.077	.053	.061	.045	.031	.020	.015	.010	
4.0	.171	.115	.071	.147	.099	.062	.101	.069	.044	.058	.040	.026	.019	.013	.008	
5.0	.164	.104	.060	.141	.090	.052	.097	.063	.037	.056	.037	.022	.018	.012	.007	
6.0	.157	.096	.052	.135	.083	.046	.093	.058	.032	.054	.034	.019	.017	.011	.006	
7.0	.150	.089	.047	.129	.077	.041	.089	.054	.029	.052	.032	.017	.017	.010	.006	
8.0	.143	.083	.042	.123	.072	.037	.085	.051	.026	.050	.030	.016	.016	.010	.005	
9.0	.137	.078	.039	.118	.068	.034	.082	.048	.024	.048	.028	.014	.015	.009	.005	
10.0	.131	.074	.036	.113	.064	.031	.079	.045	.022	.046	.027	.013	.015	.009	.004	

C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2021-01-21

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

UGR(Unified Glare Rating) Table

Test:U:24.00V I:0.1740A P:4.176W PF:1.000 Freq:0Hz Lamp Flux:897.69lx1 lm											
NAME: D8902410NO						TYPE:		WEIGHT:			
SPEC.:D8902410NO-8NWNSA012WC0100						DIM.: 1000*10*1.5mm		SERIAL No.:			
MFR.: COLORS						SUR.:1000*10mm		Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	24.8	26.3	25.1	26.5	26.8	25.0	26.5	25.3	26.7	27.0	
	3H	26.3	27.7	26.6	28.0	28.2	26.6	28.0	26.9	28.3	28.6
	4H	26.9	28.2	27.2	28.5	28.8	27.3	28.6	27.6	28.9	29.2
	6H	27.2	28.5	27.6	28.8	29.1	27.7	29.0	28.1	29.3	29.6
	8H	27.3	28.5	27.7	28.8	29.2	27.8	29.1	28.2	29.4	29.7
	12H	27.3	28.5	27.7	28.8	29.2	27.9	29.1	28.3	29.4	29.7
4H	2H	25.4	26.7	25.8	27.0	27.3	25.6	26.9	25.9	27.2	27.5
	3H	27.1	28.3	27.5	28.6	29.0	27.4	28.6	27.8	28.9	29.2
	4H	27.8	28.9	28.2	29.2	29.6	28.1	29.2	28.6	29.6	29.9
	6H	28.3	29.2	28.7	29.6	30.0	28.7	29.7	29.1	30.0	30.5
	8H	28.4	29.3	28.8	29.7	30.1	28.9	29.8	29.3	30.2	30.6
	12H	28.5	29.3	28.9	29.7	30.1	29.0	29.8	29.5	30.2	30.7
8H	4H	28.1	29.0	28.5	29.4	29.8	28.4	29.3	28.8	29.7	30.1
	6H	28.7	29.4	29.2	29.9	30.3	29.1	29.8	29.6	30.3	30.7
	8H	28.9	29.5	29.4	30.0	30.5	29.3	30.0	29.8	30.5	30.9
	12H	29.0	29.6	29.5	30.1	30.6	29.5	30.1	30.0	30.6	31.1
12H	4H	28.1	28.9	28.5	29.3	29.8	28.4	29.2	28.8	29.6	30.1
	6H	28.7	29.4	29.2	29.8	30.3	29.1	29.8	29.6	30.2	30.7
	8H	29.0	29.5	29.5	30.0	30.5	29.4	30.0	29.9	30.5	31.0
Variations with the observer position at spacings:											
S = 1.0H	+ 0.1 / - 0.2					+ 0.1 / - 0.2					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					
2.0H	+ 0.2 / - 0.4					+ 0.2 / - 0.3					

CIE Pub.117, 897.7 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -0.4)

C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2021-01-21

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

UTILIZATION FACTORS TABLE

Test:U:24.00V I:0.1740A P:4.176W PF:1.000 Freq:0Hz Lamp Flux:897.69lx1 lm		
NAME: D8902410NO	TYPE:	WEIGHT:
SPEC.:D8902410NO-8NWNSA012WC0100	DIM.: 1000*10*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*10mm	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	56	44	37	55	44	37	54	43	37	30
0.80	66	54	47	65	54	46	63	53	46	39
1.00	74	63	56	73	62	55	71	64	55	47
1.25	82	71	63	80	70	63	77	68	62	54
1.50	87	77	69	85	76	69	82	74	68	60
2.00	94	85	78	92	84	77	88	81	76	67
2.50	98	90	84	96	88	83	91	85	80	72
3.00	101	94	88	99	92	87	95	89	85	76
4.00	105	99	95	103	98	93	98	94	90	81
5.00	108	103	99	105	101	97	100	97	94	84
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG  
 C Interval: 45.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:JYH  
 Test Date:2021-01-21

g Range: 0 - 180DEG  
 g Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
 Humidity:65.0%  
 Test Distance:10.950m [K=1.0000]  
 Remarks:

### ISOCANDELA DIAGRAM

Test:U:24.00V I:0.1740A P:4.176W PF:1.000 Freq:0Hz Lamp Flux:897.69lx1 lm		
NAME: D8902410NO	TYPE:	WEIGHT:
SPEC.:D8902410NO-8NWNSA012WC0100	DIM.: 1000*10*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*10mm	Shielding Angle:



C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2021-01-21


deg Range: 0 - 180DEG  
Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:



### AAI Figure

Test:U:24.00V I:0.1740A P:4.176W PF:1.000 Freq:0Hz Lamp Flux:897.69lx1 lm		
NAME: D8902410NO	TYPE:	WEIGHT:
SPEC.:D8902410NO-8NWNSA012WC0100	DIM.: 1000*10*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*10mm	Shielding Angle:

Flux out:682.2 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2021-01-21

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

### ISOLUX DIAGRAM


Test:U:24.00V I:0.1740A P:4.176W PF:1.000 Freq:0Hz Lamp Flux:897.69lx1 lm		
NAME: D8902410NO	TYPE:	WEIGHT:
SPEC.:D8902410NO-8NWNSA012WC0100	DIM.: 1000*10*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*10mm	Shielding Angle:



C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2021-01-21

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

### Planar Illuminance Curve



C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators: JYH  
Test Date: 2021-01-21

deg Range: 0 - 180DEG  
deg Interval: 1.0DEG  
Test System: EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity: 65.0%  
Test Distance: 10.950m [K=1.0000]  
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:24.00V I:0.1740A P:4.176W PF:1.000 Freq:0Hz Lamp Flux:897.69lx1 lm		
NAME: D8902410NO	TYPE:	WEIGHT:
SPEC.:D8902410NO-8NWN5A012WC0100	DIM.: 1000*10*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*10mm	Shielding Angle:

Table--1

UNIT: cd

C(DEG) g (DEG)	0	45	90	135	180	225	270	315										
0	288	289	289	289	288	289	289	289										
5	287	288	288	289	288	288	287	287										
10	283	284	285	287	285	285	284	283										
15	277	279	281	282	281	280	278	277										
20	270	272	274	276	274	273	270	269										
25	260	262	265	268	265	263	261	259										
30	248	251	254	257	255	252	249	246										
35	234	238	241	245	242	239	235	232										
40	219	222	226	230	227	223	219	216										
45	201	205	209	213	210	206	202	198										
50	181	185	190	194	191	187	183	178										
55	159	163	168	173	170	166	161	157										
60	136	140	145	150	147	143	138	133										
65	111	115	120	125	122	118	113	109										
70	84.3	88.1	93.1	98.2	95.6	91.7	87.3	82.3										
75	57.5	60.9	65.5	70.6	68.3	64.8	60.8	56.0										
80	32.1	35.0	38.8	43.5	41.5	38.7	35.2	31.1										
85	11.7	13.8	16.3	19.9	17.9	16.4	14.1	11.4										
90	2.06	2.62	2.67	4.77	3.62	3.03	1.37	1.81										
95	1.24	1.28	1.24	1.35	0.65	0.72	0.45	0.69										
100	1.25	1.29	1.20	1.28	0.83	0.81	0.81	0.86										
105	1.50	1.50	1.24	1.46	1.26	1.21	1.24	1.28										
110	1.88	1.83	1.51	1.77	1.70	1.57	1.63	1.74										
115	2.32	2.25	1.93	2.16	2.11	1.92	1.93	2.17										
120	2.71	2.65	2.33	2.52	2.53	2.29	2.19	2.54										
125	3.08	2.97	2.67	2.84	2.91	2.56	2.41	2.76										
130	3.39	3.24	2.97	3.13	3.20	2.82	2.62	2.99										
135	3.70	3.46	3.20	3.37	3.49	3.10	2.78	3.08										
140	3.91	3.64	3.39	3.55	3.71	3.29	2.93	3.17										
145	4.06	3.76	3.59	3.75	3.90	3.53	3.07	3.23										
150	4.15	3.86	3.72	3.92	4.03	3.77	3.31	3.31										
155	4.33	3.94	3.86	4.12	4.20	4.00	3.67	3.33										
160	4.47	4.04	4.13	4.33	4.34	4.19	4.08	3.54										
165	4.56	4.20	4.47	4.51	4.45	4.36	4.42	3.95										
170	4.59	4.53	4.76	4.72	4.35	4.58	4.76	4.39										
175	4.43	4.86	5.02	4.98	4.22	4.79	5.05	4.89										
180	4.48	5.12	5.21	5.31	4.48	5.13	5.25	5.32										

C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2021-01-21

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks: