


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:48.00V I:0.0580A P:2.780W PF:1.000 Freq:0Hz Lamp Flux:106.242x1 lm		
NAME: NMS1217-Plus	TYPE:	WEIGHT:
SPEC.:NMS1217-0RGBLW48CSN050CC0100-Plus	DIM.: 1000*12*17	SERIAL No.:01
MFR.: COLORS	SUR.:1000*12	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 38.22 lm/W			
MODEL	NMS1217-Plus	I _{max} (cd)	34.35	S/MH(C0/180)	1.22
NOMINAL POWER(W)	9.6	LOR(%)	100.0	S/MH(C90/270)	1.24
RATED VOLTAGE(V)	48	TOTAL FLUX(lm)	106.24	h UP,DN(C0-180)	2.4,49.9
NOMINAL FLUX(lm)	106.242	CIE CLASS	DIRECT	h UP,DN(C180-360)	2.0,45.8
LAMPS INSIDE	1	h up(%)	4.4	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	48	h down(%)	95.6	CIBSE SHR MAX	1.35

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-06-15

g Range: 0 - 180DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	34.32	34.10	33.64	33.34	33.29	33.20	33.42	34.13	0- 10	3.241	3.241	3.05,3.05
20	33.35	33.00	31.77	31.22	31.19	30.94	31.43	32.87	10- 20	9.307	12.55	11.8,11.8
30	31.17	30.76	28.71	27.95	27.97	27.58	28.29	30.51	20- 30	14.14	26.69	25.1,25.1
40	27.94	27.44	24.74	23.77	23.83	23.37	24.30	27.10	30- 40	17.09	43.78	41.2,41.2
50	23.90	23.30	20.03	18.83	18.90	18.40	19.60	22.91	40- 50	17.82	61.59	58,58
60	19.18	18.50	14.78	13.36	13.43	12.94	14.39	18.10	50- 60	16.28	77.88	73.3,73.3
70	13.96	13.21	9.173	7.586	7.691	7.266	8.853	12.83	60- 70	12.72	90.60	85.3,85.3
80	8.453	7.651	3.646	2.541	2.795	2.399	3.511	7.381	70- 80	7.765	98.36	92.6,92.6
90	3.587	2.793	0.2678	1.156	1.583	1.196	0.2598	2.705	80- 90	3.243	101.6	95.6,95.6
100	2.017	1.389	0.1413	0.9416	1.369	0.9956	0.1335	1.303	90-100	1.375	103.0	96.9,96.9
110	1.730	1.095	0.1535	0.7149	1.149	0.7752	0.1805	1.182	100-110	1.002	104.0	97.9,97.9
120	1.377	0.6865	0.2270	0.4074	0.8614	0.4612	0.2408	0.6686	110-120	0.7544	104.7	98.6,98.6
130	0.9153	0.4408	0.3073	0.4008	0.5872	0.3674	0.2939	0.3944	120-130	0.4754	105.2	99,99
140	0.7019	0.4342	0.3939	0.4275	0.4542	0.3807	0.3473	0.3540	130-140	0.3421	105.6	99.4,99.4
150	0.5745	0.4476	0.4141	0.4609	0.4609	0.4141	0.4011	0.3674	140-150	0.2771	105.8	99.6,99.6
160	0.5477	0.4875	0.4607	0.5345	0.4878	0.4807	0.4878	0.3942	150-160	0.2131	106.0	99.8,99.8
170	0.5477	0.5412	0.5277	0.5678	0.5010	0.5143	0.5813	0.4942	160-170	0.1446	106.2	99.9,99.9
180	0.5410	0.6279	0.6412	0.6346	0.5277	0.6211	0.6479	0.6412	170-180	0.0534	106.2	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-06-15

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

LUMINANCE LIMITATION CURVES

Test:U:48.00V I:0.0580A P:2.780W PF:1.000 Freq:0Hz Lamp Flux:106.242x1 lm		
NAME: NMS1217-Plus	TYPE:	WEIGHT:
SPEC.:NMS1217-0RGBLW48CSN050CC0100-Plus	DIM.: 1000*12*17	SERIAL No.:01
MFR.: COLORS	SUR.:1000*12	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-06-15

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:48.00V I:0.0580A P:2.780W PF:1.000 Freq:0Hz Lamp Flux:106.242x1 lm		
NAME: NMS1217-Plus	TYPE:	WEIGHT:
SPEC.:NMS1217-0RGBLW48CSN050CC0100-Plus	DIM.: 1000*12*17	SERIAL No.:01
MFR.: COLORS	SUR.:1000*12	Shielding Angle:

r _{cc}	80%			70%			50%			30%			10%			0
r _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Coefficients of Utilization(CU)												
0.0	1.18	1.18	1.18	1.15	1.15	1.15	1.09	1.09	1.09	1.03	1.03	1.03	.98	.98	.98	.96
1.0	1.02	.98	.94	.99	.95	.92	.94	.91	.88	.90	.87	.84	.85	.83	.81	.79
2.0	.89	.82	.76	.86	.80	.74	.82	.77	.72	.78	.74	.70	.74	.71	.67	.65
3.0	.78	.69	.63	.76	.68	.62	.72	.65	.60	.69	.63	.58	.66	.61	.57	.55
4.0	.69	.60	.53	.67	.59	.52	.64	.57	.51	.61	.55	.50	.58	.53	.49	.46
5.0	.61	.52	.45	.60	.51	.45	.57	.50	.44	.55	.48	.43	.52	.47	.42	.40
6.0	.55	.46	.39	.54	.45	.39	.52	.44	.38	.49	.43	.38	.47	.42	.37	.35
7.0	.50	.41	.35	.49	.40	.34	.47	.39	.34	.45	.38	.33	.43	.37	.33	.31
8.0	.45	.37	.31	.45	.36	.31	.43	.35	.30	.41	.35	.30	.40	.34	.29	.27
9.0	.42	.33	.28	.41	.33	.28	.39	.32	.27	.38	.32	.27	.37	.31	.26	.25
10.0	.38	.30	.25	.38	.30	.25	.36	.29	.25	.35	.29	.24	.34	.28	.24	.22



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-06-15

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:48.00V I:0.0580A P:2.780W PF:1.000 Freq:0Hz Lamp Flux:106.242x1 lm		
NAME: NMS1217-Plus	TYPE:	WEIGHT:
SPEC.:NMS1217-0RGBLW48CSN050CC0100-Plus	DIM.: 1000*12*17	SERIAL No.:01
MFR.: COLORS	SUR.:1000*12	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio															

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.224	.224	.224	.191	.191	.191	.131	.131	.131	.075	.075	.075	.024	.024	.024	
1.0	.215	.190	.167	.184	.163	.144	.126	.112	.099	.072	.065	.058	.023	.021	.019	
2.0	.207	.166	.131	.177	.143	.113	.121	.099	.079	.070	.057	.046	.022	.019	.015	
3.0	.199	.148	.108	.171	.128	.093	.117	.089	.065	.068	.052	.039	.022	.017	.013	
4.0	.192	.135	.092	.164	.117	.080	.113	.081	.056	.065	.048	.033	.021	.016	.011	
5.0	.184	.125	.081	.158	.108	.071	.109	.075	.050	.063	.044	.030	.020	.014	.010	
6.0	.177	.117	.073	.152	.101	.064	.105	.071	.045	.061	.042	.027	.020	.014	.009	
7.0	.170	.110	.067	.146	.095	.059	.101	.067	.042	.059	.039	.025	.019	.013	.008	
8.0	.164	.104	.063	.141	.090	.055	.097	.063	.039	.057	.037	.023	.018	.012	.008	
9.0	.158	.099	.060	.136	.086	.052	.094	.060	.037	.055	.036	.022	.018	.012	.007	
10.0	.152	.095	.057	.131	.082	.050	.091	.058	.035	.053	.034	.021	.017	.011	.007	

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-06-15

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:48.00V I:0.0580A P:2.780W PF:1.000 Freq:0Hz Lamp Flux:106.242x1 lm										
NAME: NMS1217-Plus					TYPE:			WEIGHT:		
SPEC.:NMS1217-0RGBLW48CSN050CC0100-Plus					DIM.: 1000*12*17			SERIAL No.:01		
MFR.: COLORS					SUR.:1000*12			Shielding Angle:		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	25.0	26.4	25.3	26.7	27.0	24.1	25.5	24.4	25.8	26.1
3H	26.9	28.3	27.3	28.6	28.9	25.6	26.9	25.9	27.3	27.6
4H	27.9	29.2	28.3	29.5	29.9	26.2	27.5	26.5	27.8	28.1
6H	28.8	30.0	29.2	30.4	30.7	26.6	27.8	27.0	28.1	28.5
8H	29.2	30.4	29.6	30.7	31.1	26.7	27.9	27.1	28.2	28.6
12H	29.6	30.8	30.0	31.1	31.5	26.7	27.9	27.1	28.2	28.6
4H 2H	25.6	26.9	26.0	27.2	27.6	24.9	26.2	25.3	26.6	26.9
3H	27.8	28.9	28.2	29.3	29.7	26.7	27.8	27.1	28.2	28.6
4H	28.9	29.9	29.3	30.3	30.8	27.5	28.5	27.9	28.9	29.3
6H	30.0	30.9	30.4	31.3	31.8	28.0	28.9	28.5	29.4	29.8
8H	30.5	31.3	31.0	31.8	32.3	28.2	29.1	28.7	29.5	30.0
12H	31.0	31.8	31.5	32.3	32.8	28.3	29.1	28.8	29.5	30.0
8H 4H	29.3	30.1	29.7	30.6	31.0	28.0	28.9	28.5	29.3	29.8
6H	30.5	31.3	31.1	31.7	32.3	28.9	29.6	29.4	30.1	30.6
8H	31.2	31.8	31.7	32.3	32.9	29.2	29.8	29.7	30.3	30.8
12H	31.9	32.5	32.5	33.0	33.6	29.4	29.9	29.9	30.5	31.0
12H 4H	29.3	30.1	29.8	30.5	31.0	28.1	28.9	28.6	29.4	29.9
6H	30.6	31.3	31.2	31.8	32.3	29.1	29.7	29.6	30.2	30.8
8H	31.4	31.9	31.9	32.5	33.0	29.5	30.0	30.0	30.6	31.1
Variations with the observer position at spacings:										
S = 1.0H	+ 0.1 / - 0.1					+ 0.1 / - 0.2				
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.4				
2.0H	+ 0.1 / - 0.3					+ 0.2 / - 0.5				

CIE Pub.117, 106.2 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -7.8)

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-06-15

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:48.00V I:0.0580A P:2.780W PF:1.000 Freq:0Hz Lamp Flux:106.242x1 lm		
NAME: NMS1217-Plus	TYPE:	WEIGHT:
SPEC.:NMS1217-0RGBLW48CSN050CC0100-Plus	DIM.: 1000*12*17	SERIAL No.:01
MFR.: COLORS	SUR.:1000*12	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	55	44	37	55	43	36	53	43	36	30
0.80	65	53	46	64	53	46	62	52	45	38
1.00	74	62	55	72	61	54	70	63	53	46
1.25	81	70	62	79	69	62	76	67	61	53
1.50	86	75	68	84	74	67	80	72	66	58
2.00	93	83	77	90	82	76	86	79	74	65
2.50	97	88	82	94	87	81	90	84	78	69
3.00	100	93	87	98	91	85	93	87	83	73
4.00	104	98	93	101	96	91	96	92	88	78
5.00	107	101	97	104	99	95	99	95	91	81
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-06-15

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:48.00V I:0.0580A P:2.780W PF:1.000 Freq:0Hz Lamp Flux:106.242x1 lm		
NAME: NMS1217-Plus	TYPE:	WEIGHT:
SPEC.:NMS1217-0RGBLW48CSN050CC0100-Plus	DIM.: 1000*12*17	SERIAL No.:01
MFR.: COLORS	SUR.:1000*12	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2020-06-15

Range: 0 - 180DEG
Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

AAI Figure

Test:U:48.00V I:0.0580A P:2.780W PF:1.000 Freq:0Hz Lamp Flux:106.242x1 lm		
NAME: NMS1217-Plus	TYPE:	WEIGHT:
SPEC.:NMS1217-0RGBLW48CSN050CC0100-Plus	DIM.: 1000*12*17	SERIAL No.:01
MFR.: COLORS	SUR.:1000*12	Shielding Angle:

Flux out:71.69 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-06-15

g Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


Test:U:48.00V I:0.0580A P:2.780W PF:1.000 Freq:0Hz Lamp Flux:106.242x1 lm		
NAME: NMS1217-Plus	TYPE:	WEIGHT:
SPEC.:NMS1217-0RGBLW48CSN050CC0100-Plus	DIM.: 1000*12*17	SERIAL No.:01
MFR.: COLORS	SUR.:1000*12	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-06-15

Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2020-06-15

deg Range: 0 - 180DEG
Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:48.00V I:0.0580A P:2.780W PF:1.000 Freq:0Hz Lamp Flux:106.242x1 lm		
NAME: NMS1217-Plus	TYPE:	WEIGHT:
SPEC.:NMS1217-0RGBLW48CSN050CC0100-Plus	DIM.: 1000*12*17	SERIAL No.:01
MFR.: COLORS	SUR.:1000*12	Shielding Angle:

Table--1

UNIT: cd

C(DEG) g (DEG)	0	45	90	135	180	225	270	315										
0	34.2	34.2	34.2	34.3	34.2	34.2	34.2	34.3										
5	34.3	34.3	34.1	33.9	33.9	33.9	33.9	34.3										
10	34.3	34.1	33.6	33.3	33.3	33.2	33.4	34.1										
15	34.0	33.7	32.9	32.4	32.4	32.2	32.6	33.6										
20	33.3	33.0	31.8	31.2	31.2	30.9	31.4	32.9										
25	32.4	32.0	30.4	29.7	29.7	29.4	30.0	31.8										
30	31.2	30.8	28.7	27.9	28.0	27.6	28.3	30.5										
35	29.7	29.2	26.8	26.0	26.0	25.6	26.4	28.9										
40	27.9	27.4	24.7	23.8	23.8	23.4	24.3	27.1										
45	26.0	25.5	22.4	21.4	21.4	20.9	22.0	25.1										
50	23.9	23.3	20.0	18.8	18.9	18.4	19.6	22.9										
55	21.6	21.0	17.5	16.2	16.3	15.7	17.1	20.6										
60	19.2	18.5	14.8	13.4	13.4	12.9	14.4	18.1										
65	16.6	15.9	12.0	10.5	10.6	10.1	11.6	15.5										
70	14.0	13.2	9.17	7.59	7.69	7.27	8.85	12.8										
75	11.2	10.4	6.31	4.84	4.98	4.61	6.10	10.1										
80	8.45	7.65	3.65	2.54	2.80	2.40	3.51	7.38										
85	5.85	4.99	1.37	1.35	1.70	1.32	1.27	4.82										
90	3.59	2.79	0.27	1.16	1.58	1.20	0.26	2.71										
95	2.28	1.58	0.24	1.06	1.47	1.10	0.22	1.64										
100	2.02	1.39	0.14	0.94	1.37	1.00	0.13	1.30										
105	1.81	1.25	0.13	0.83	1.26	0.89	0.15	1.26										
110	1.73	1.10	0.15	0.71	1.15	0.78	0.18	1.18										
115	1.58	0.92	0.20	0.60	1.03	0.56	0.21	1.02										
120	1.38	0.69	0.23	0.41	0.86	0.46	0.24	0.67										
125	1.12	0.52	0.31	0.39	0.72	0.37	0.27	0.45										
130	0.92	0.44	0.31	0.40	0.59	0.37	0.29	0.39										
135	0.78	0.43	0.33	0.41	0.50	0.37	0.32	0.37										
140	0.70	0.43	0.39	0.43	0.45	0.38	0.35	0.35										
145	0.63	0.43	0.41	0.45	0.45	0.41	0.37	0.37										
150	0.57	0.45	0.41	0.46	0.46	0.41	0.40	0.37										
155	0.56	0.47	0.41	0.51	0.47	0.44	0.45	0.39										
160	0.55	0.49	0.46	0.53	0.49	0.48	0.49	0.39										
165	0.55	0.51	0.53	0.56	0.50	0.51	0.54	0.41										
170	0.55	0.54	0.53	0.57	0.50	0.51	0.58	0.49										
175	0.55	0.59	0.61	0.61	0.51	0.53	0.62	0.51										
180	0.54	0.63	0.64	0.63	0.53	0.62	0.65	0.64										

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-06-15

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks: